

SBC58BLBIADAIFCMTWIN



32.25" x 23.63" x 22.75" (H x W x D)

Built-in undercounter ADA height commercially listed dual tap combo nitro/cold brew coffee dispenser with panelready door and black cabinet

Highlights:

32 inch height fits under lower ADA compliant counters

Commercial grade tap kit includes everything you need to serve both flat iced cold brew and creamy nitro brew drafts

Commercially listed to NSF-7 standards

Product Features:

Dispenses both flat and nitro coffee	Unique combination stout and standard tap system allows you to serve both flat iced cold brew and nitro drafts
ADA compliant height	Sized at 32 inches high (32.25 to hinge cap) for installation under lower ADA compliant counters
Commercially approved	ETL-S listed to NSF-7 commercial standards and meets UL-471 for use in foodservice settings
Built-in capable	Front-breathing design lets you make the best use of space by installing your appliance under the counter
Complete tap kit	Commercial grade tap kit includes a dual tap draft tower with a standard and stout tap, Nitrogen tank, dual gauge regulator, and connections for ball lock Cornelius kegs
Dual tap system	Twin style draft tower allows you to serve from two cornelius style kegs
Panel-ready door	Customize the front by mounting an overlay panel over the door; seamless look can blend into other cabinetry with no exposed frame. Handle not included (panel size: 23 5/16" W x 28 1/4" H and at least 3/4" thick; maximum weight: 10 lbs.)
Adjustable thermostat	Interior dial thermostat ensures easy temperature management



SBC58BLBIADAIFCMTWIN Specifications:

Overview			
Nominal Height	32.0" (81 cm)		
Height of Cabinet	32.0" (81 cm)		
Height to Hinge Cap	32.25" (82 cm)		
Nominal Width	24.0" (61 cm)		
Width	23.63" (60 cm)		
Nominal Depth	23.0" (58 cm)		
Depth	22.75" (58 cm)		
Depth with door at 90°	45.0" (114 cm)		
Capacity	5.5 cu.ft. (156 L)		
Defrost Type	Automatic		
Door	Panel-Ready		
Cabinet	Black		
US Electrical Safety	ETL		
Canadian Electrical Safety	ETL-C		
Sanitation	ETL-S		
Amps	1.2		
Voltage/Frequency	115 V AC/60 Hz		
Weight	110.0 lbs. (50 kg)		
Parts & Labor Warranty	1 Year		
Compressor Warranty	5 Years		
UPC	761101069678		
Kegerator			
3			
Door Swing	RHD		
	RHD Factory Reversible		
Door Swing			
Door Swing Reversible	Factory Reversible		
Door Swing Reversible Tap Kit	Factory Reversible Yes		
Door Swing Reversible Tap Kit Number of Taps	Factory Reversible Yes 2		
Door Swing Reversible Tap Kit Number of Taps Thermostat Type	Factory Reversible Yes 2 Dial		
Door Swing Reversible Tap Kit Number of Taps Thermostat Type Interior Light	Factory Reversible Yes 2 Dial Yes		
Door Swing Reversible Tap Kit Number of Taps Thermostat Type Interior Light Fan Type	Factory Reversible Yes 2 Dial Yes Exterior		
Door Swing Reversible Tap Kit Number of Taps Thermostat Type Interior Light Fan Type Refrigerant	Factory Reversible Yes 2 Dial Yes Exterior R600a		
Door Swing Reversible Tap Kit Number of Taps Thermostat Type Interior Light Fan Type Refrigerant Refrigerant Amount	Factory Reversible Yes 2 Dial Yes Exterior R600a 0.64 oz.		
Door Swing Reversible Tap Kit Number of Taps Thermostat Type Interior Light Fan Type Refrigerant Refrigerant Amount High Side PSI	Factory Reversible Yes 2 Dial Yes Exterior R600a 0.64 oz. 180.0		
Door Swing Reversible Tap Kit Number of Taps Thermostat Type Interior Light Fan Type Refrigerant Refrigerant Amount High Side PSI Low Side PSI	Factory Reversible Yes 2 Dial Yes Exterior R600a 0.64 oz. 180.0		
Door Swing Reversible Tap Kit Number of Taps Thermostat Type Interior Light Fan Type Refrigerant Refrigerant Amount High Side PSI Low Side PSI Inter Height	Factory Reversible Yes 2 Dial Yes Exterior R600a 0.64 oz. 180.0 80.0 25.75" (65 cm)		

Compressor Step Width	21.0" (53 cm)
Compressor Step Depth	5.5" (14 cm)
Temperature Range	34º to 43ºF

