

## **SBC58BLBIADAIFNCFTWIN**



32.25" x 23.63" x 22.75" (H x W x D)

Built-in undercounter ADA height commercially listed dual tap nitro coffee dispenser with panel-ready door and black cabinet

## **Highlights:**

32 inch height fits under lower ADA compliant counters

Commercial grade dual style tap kit includes everything you need to serve creamy nitro coffee on draft

Commercially listed to NSF-7 standards

## **Product Features:**

Dispenses nitro coffee	Stout style tap allows you to serve smooth nitro cold brew on tap	
ADA compliant height	Sized at 32 inches high (32.25 to hinge cap) for installation under lower ADA compliant counters	
Commercially approved	ETL-S listed to NSF-7 commercial standards and meets UL-471 for use in foodservice settings	
Built-in capable	Front-breathing design lets you make the best use of space by installing your appliance under the counter	
Complete tap kit	Commercial grade tap kit includes a stainless steel stout tower, Nitrogen tank, regulator, and connections for ball lock cornelius kegs	
Dual tap system	Twin style draft tower allows you to serve from two cornelius style kegs	
Panel-ready door	Customize the front by mounting an overlay panel over the door; seamless look can blend into other cabinetry with no exposed frame. Handle not included (panel size: 23 5/16" W x 28 1/4" H and at least 3/4" thick; maximum weight: 10 lbs.)	
Adjustable thermostat	Interior dial thermostat ensures easy temperature management	
Automatic defrost	No-frost operation for minimum user maintenance	
SUMMIT APPLIANCE DIVISION FEL	IX STORCH INC LISO 9001:2015 Certified	



## SBC58BLBIADAIFNCFTWIN Specifications:

Overview			
Nominal Height	32.0" (81 cm)		
Height of Cabinet	32.0" (81 cm)		
Height to Hinge Cap	32.25" (82 cm)		
Nominal Width	24.0" (61 cm)		
Width	23.63" (60 cm)		
Nominal Depth	23.0" (58 cm)		
Depth	22.75" (58 cm)		
Depth with door at 90°	45.0" (114 cm)		
Capacity	5.5 cu.ft. (156 L)		
Defrost Type	Automatic		
Door	Panel-Ready		
Cabinet	Black		
US Electrical Safety	ETL		
Canadian Electrical Safety	ETL-C		
Sanitation	ETL-S		
Amps	1.2		
Voltage/Frequency	115 V AC/60 Hz		
Weight	110.0 lbs. (50 kg)		
Parts & Labor Warranty	1 Year		
Compressor Warranty	5 Years		
UPC	761101069685		
Kegerator			
Door Swing	RHD		
Reversible	Factory Reversible		
Tap Kit	Yes		
Number of Taps	2		
Thermostat Type	Dial		
Interior Light	Yes		
Fan Type	Exterior		
Refrigerant	R600a		
Refrigerant Amount	0.64 oz.		
High Side PSI	180.0		
Low Side PSI	80.0		
Inter Height	25.75" (65 cm)		
Interior Width	21.0" (53 cm)		
Interior Depth	17.75" (45 cm)		
Compressor Step Height	6.5" (17 cm)		

Compressor Step Width	21.0" (53 cm)
Compressor Step Depth	5.5" (14 cm)
Temperature Range	34º to 43ºF

