

SBC58BLBIADANCFTWIN



32.25" x 23.63" x 22.75" (H x W x D)

Built-in undercounter ADA height commercially listed dual tap nitro coffee dispenser with stainless steel wrapped door and black cabinet

Highlights:

32 inch height fits under lower ADA compliant counters

Commercial grade dual style tap kit includes everything you need to serve creamy nitro coffee on draft

Commercially listed to NSF-7 standards

Product Features:

Dispenses nitro coffee	Stout style tap allows you to serve smooth nitro cold brew on tap	
ADA compliant height	Sized at 32 inches high (32.25 to hinge cap) for installation under lower ADA compliant counters	
Built-in capable	Front-breathing design allows fully recessed installation under counters	
Commercially approved	ETL-S listed to NSF-7 commercial standards and meets UL-471 for use in foodservice settings	
Complete tap kit	Commercial grade tap kit includes a stainless steel stout tower, Nitrogen tank, regulator, and connections for ball lock cornelius kegs	
Dual tap system	Twin style draft tower allows you to serve from two cornelius style kegs	
Stainless steel wrapped door	304 grade stainless steel for a professional look with lasting durability	
Professional handle	Thin handle with common 14mm diameter in brushed stainless steel mounted horizontally	
Adjustable thermostat	Interior dial thermostat ensures easy temperature management	





SBC58BLBIADANCFTWIN Specifications:

Overview			
Height of Cabinet	32.0" (81 cm)		
Height to Hinge Cap	32.25" (82 cm)		
Width	23.63" (60 cm)		
Depth	22.75" (58 cm)		
Depth with Handle	24.25" (62 cm)		
Depth with door at 90°	45.0" (114 cm)		
Capacity	5.5 cu.ft. (156 L)		
Defrost Type	Automatic		
Door	Stainless Steel		
Cabinet	Black		
US Electrical Safety	ETL		
Canadian Electrical Safety	ETL-C		
Sanitation	ETL-S		
Amps	1.2		
Voltage/Frequency	115 V AC/60 Hz		
Weight	110.0 lbs. (50 kg)		
Shipping Weight	144.5 lbs. (66 kg)		
Parts & Labor Warranty	1 Year		
Compressor Warranty	5 Years		
UPC	761101069708		
Kegerator			
Door Swing	RHD		
Reversible	Yes		
Tap Kit	.,		
•	Yes		
Number of Taps	Yes 2		
			
Number of Taps	2		
Number of Taps Thermostat Type	2 Dial		
Number of Taps Thermostat Type Interior Light	2 Dial Yes		
Number of Taps Thermostat Type Interior Light Fan Type	Dial Yes Exterior		
Number of Taps Thermostat Type Interior Light Fan Type Refrigerant	Dial Yes Exterior R600a		
Number of Taps Thermostat Type Interior Light Fan Type Refrigerant Refrigerant Amount	Dial Yes Exterior R600a 0.64 oz.		
Number of Taps Thermostat Type Interior Light Fan Type Refrigerant Refrigerant Amount High Side PSI	Dial Yes Exterior R600a 0.64 oz. 180.0		
Number of Taps Thermostat Type Interior Light Fan Type Refrigerant Refrigerant Amount High Side PSI Low Side PSI	2 Dial Yes Exterior R600a 0.64 oz. 180.0 80.0		
Number of Taps Thermostat Type Interior Light Fan Type Refrigerant Refrigerant Amount High Side PSI Low Side PSI Inter Height	2 Dial Yes Exterior R600a 0.64 oz. 180.0 80.0 25.75" (65 cm)		
Number of Taps Thermostat Type Interior Light Fan Type Refrigerant Refrigerant Amount High Side PSI Low Side PSI Inter Height Interior Width	2 Dial Yes Exterior R600a 0.64 oz. 180.0 80.0 25.75" (65 cm) 21.0" (53 cm)		

Compressor Step Depth	5.5" (14 cm)
Temperature Range	34° to 43°F

