

SBC58BLBIADANK



32.25" x 23.63" x 23.5" (H x W x D)

Built-in undercounter ADA height commercially listed kegerator with stainless steel wrapped door and black cabinet; no tapping equipment included

Highlights:

32 inch height fits under lower ADA compliant counters

Commercially listed to NSF-7 standards

Flexible design allows built-in or freestanding use in 24" spaces

Product Features:

ADA compliant height	Sized at 32 inches high (32.25 to hinge cap) for installation under lower ADA compliant counters	
Commercially approved	ETL-S listed to NSF-7 commercial standards and meets UL-471 for use in foodservice settings	
Built-in capable	Front-breathing design allows fully recessed installation under counters	
Designed for 1/6 kegs	Interior can store up to two sixtel kegs	
Tap kit not included	Install your own tapping equipment to create a customized beer cooler	
Stainless steel wrapped door	304 grade stainless steel for a professional look with lasting durability	
Professional handle	Thin handle with common 14mm diameter in brushed stainless steel mounted horizontally	
Adjustable thermostat	Interior dial thermostat ensures easy temperature management	
Automatic defrost	No-frost operation for minimum user maintenance	

 \checkmark






SBC58BLBIADANK Specifications:

Overview	
Nominal Height	32.0" (81 cm)
Height of Cabinet	32.0" (81 cm)
Height to Hinge Cap	32.25" (82 cm)
Nominal Width	24.0" (61 cm)
Width	23.63" (60 cm)
Nominal Depth	24.0" (61 cm)
Depth	23.5" (60 cm)
Depth with Handle	24.25" (62 cm)
Depth with door at 90°	45.0" (114 cm)
Capacity	5.5 cu.ft. (156 L)
Defrost Type	Automatic
Door	Stainless Steel
Cabinet	Black
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Amps	1.2
Voltage/Frequency	115 V AC/60 Hz
Weight	100.0 lbs. (45 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101069715
Kegerator	
Door Swing	RHD
Reversible	Yes
Thermostat Type	Dial
Interior Light	Yes
Fan Type	Exterior
Refrigerant	R600a
Refrigerant Amount	0.64 oz.
High Side PSI	180.0
Low Side PSI	80.0
Inter Height	25.75" (65 cm)
Interior Width	21.0" (53 cm)
Interior Depth	17.75" (45 cm)
Compressor Step Height	6.5" (17 cm)
Compressor Step Width	21.0" (53 cm)

Compressor Step Depth	5.5" (14 cm)
Temperature Range	34º to 43ºF



SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

