

FS24LTBC



20" x 18.5" x 17.63" (H x W x D)

Compact all-freezer for general purpose use, with pure copper handle and manual defrost with lock

Highlights:

Copper towel bar handle kills microbes in a shorter timeframe than other metals for added safety

Compact "cube" size is ideal for use on top of counters

Factory installed lock provides security you can count on

Product Features:

Copper handle	Naturally antimicrobial, the towel bar handle made from pure copper helps to protect against microbes for added safety and cleanliness
Compact size	Convenient "cube" shape is ideal for use on top of counters
Factory installed lock	Keyed lock for a secure interior
Manual defrost	Static cooling system
One-piece interior liner	Seamless interior for easier cleanup
Removable shelf	Includes one wire shelf for easier storage
Right hand door swing	For this unit with the door opening from the other side, add option "LHD"
Adjustable thermostat	Dial thermostat for easy temperature management
Flat door liner	Designed to comply with CDC guidelines

FS24LTBC Specifications:

Overview	
Height of Cabinet	19.63" (50 cm)
Height to Hinge Cap	20.0" (51 cm)
Width	18.5" (47 cm)
Depth	17.63" (45 cm)
Depth with Handle	20.13" (51 cm)
Depth with door at 90°	34.5" (88 cm)
Capacity	1.4 cu.ft. (40 L)
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Amps	1.0
Voltage/Frequency	115 V AC/60 Hz
Weight	35.0 lbs. (16 kg)
Shipping Weight	42.5 lbs. (19 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101073378
Freezer	
Door Swing	RHD
Reversible	Factory Reversible
Interior Height	14.38" (37 cm)
Interior Width	13.5" (34 cm)
Interior Depth	13.25" (34 cm)
Shelf Type	Wire
Shelf Qty	1
Thermostat Type	Dial
Refrigerant Type	R600a
Refrigerant Amount	0.8 oz.
High Side PSI	110.0
Low Side PSI	70.0
Level Legs	2
Compressor Step Height	8.5" (22 cm)
Compressor Step Width	13.5" (34 cm)
Compressor Step Depth	6.0" (15 cm)

