# SUMMIT

# FF195H34



#### 34" x 19" x 17.25" (H x W x D)

Commercially approved, ENERGY STAR certified allrefrigerator for built-in or freestanding use with a shallow 17.25" depth, stainless steel door, and front lock

#### **Highlights:**

ENERGY STAR certified performance ensures annual savings

17.25" shallow depth makes it ideal for smaller commercial and residential settings

Commercially listed to NSF-7 standards and meets UL-471 for commercial use

### **Product Features:**

| 17.25" shallow depth   | Ideal for home wet bars, island kitchens, and other applications with limited footprint space  |  |
|------------------------|--|--|
| ENERGY STAR certified  | Rated by the DOE to perform with more efficiency than federal standards require, saving your unit energy and you on higher utility costs |  |
| Commercially approved  | ETL-S listed to NSF-7 standard and meets UL-471 for use in commercial settings   |  |
| Stainless steel door   | Stainless steel door offers an elegant look  |  |
| Automatic defrost      | Reduced user maintenance with auto defrost system  |  |
| Reversible door        | User-reversible door swing makes it easy to adjust to your setting as needed   |  |
| Factory installed lock | Keyed lock offers added security, with two keys included   |  |
| Professional handle    | Stainless steel handle adds an attractive touch  |  |
| Adjustable shelves     | Three glass shelves with brake system ensures safe, optimal storage  |  |

 $\checkmark$ 



## SUMMIT

### FF195H34 Specifications:

| Overview                   |                    |  |
|----------------------------|--------------------|--|
| Nominal Height             | 34.0" (86 cm)      |  |
| Height of Cabinet          | 34.0" (86 cm)      |  |
| Nominal Width              | 19.0" (48 cm)      |  |
| Width                      | 19.0" (48 cm)      |  |
| Nominal Depth              | 18.0" (46 cm)      |  |
| Depth                      | 17.25" (44 cm)     |  |
| Depth with Handle          | 19.0" (48 cm)      |  |
| Depth with door at 90°     | 35.0" (89 cm)      |  |
| Capacity                   | 3.13 cu.ft. (89 L) |  |
| Defrost Type               | Automatic          |  |
| Door                       | Stainless Steel    |  |
| Cabinet                    | Black              |  |
| US Electrical Safety       | ETL                |  |
| Canadian Electrical Safety | ETL-C              |  |
| Sanitation                 | ETL-S              |  |
| Energy Usage/Year          | 259.0kWh/year      |  |
| Amps                       | 1.3                |  |
| Voltage/Frequency          | 115 V AC/60 Hz     |  |
| Weight                     | 70.0 lbs. (32 kg)  |  |
| Parts & Labor Warranty     | 1 Year             |  |
| Compressor Warranty        | 5 Years            |  |
| UPC                        | 761101075662       |  |
| Refrigerator Features      |                    |  |
| Door Swing                 | RHD                |  |
| Reversible                 | Yes                |  |
| Shelf Type                 | Glass              |  |
| Shelf Qty                  | 3                  |  |
| Adjustable Shelves         | Yes                |  |
| Thermostat Type            | Dial               |  |
| Fan Type                   | Interior           |  |
| Refrigerant Type           | R600a              |  |
| Refrigerant Amount         | 0.88oz.            |  |
| High Side PSI              | 320.0              |  |
| Low Side PSI               | 120.0              |  |
| Level Legs Qty             | 2                  |  |
| Interior Light             | Yes                |  |
| Temperature Range          | 34 to 50°F         |  |
| Sound Level                | 33.4 dB            |  |
|                            |                    |  |

| Dimensions             |                |
|------------------------|----------------|
| Interior Height        | 29.0" (74 cm)  |
| Interior Width         | 16.0" (41 cm)  |
| Interior Depth         | 12.75" (32 cm) |
| Compressor Step Height | 7.0" (18 cm)   |
| Compressor Step Width  | 16.0" (41 cm)  |
| Compressor Step Depth  | 6.25" (16 cm)  |
|                        |                |



