

ACR45LSTO



31.5" x 19.5" x 24.75" (H x W x D)

Pharmacy Series ADA compliant 20" wide built-in undercounter all-refrigerator for vaccine storage, frost-free with step-to-open door pedal, internal fan, external digital controls and thermometer, and lock

Highlights:

Less than 32" high to allow installation under lower ADA compliant counters

Specially designed to meet current CDC/VFC vaccine refrigeration guidelines for convenient storage in pharmacies and other healthcare facilities

External temperature readout of the current and high/low temperatures

Product Features:

| | |
|------------------------------|--|
| Vaccine refrigerator | Purpose-built to meet the recommendations of the CDC and VFC for reliable vaccine storage |
| ADA compliant | Sized just under 32" high to allow installation under lower ADA compliant counters |
| Built-in capable | Front-breathing system allows the unit to be installed under cabinets with minimum clearance |
| Slim 20" width | Full 2.65 cu.ft. capacity inside conveniently slim footprint |
| Step-to-open door pedal | Helps lessen germ spread by providing a more sanitary method of opening appliance doors, while allowing efficient access to the unit's interior for added convenience |
| External temperature readout | Includes continuous display of the current interior and high/low temperature, and can be switched from Celsius to Fahrenheit at the touch of a button |
| Digital thermostat | Digital microprocessor for easy and precise temperature management, with all controls externally located for added convenience |
| High/low temperature alarm | Audible alarm sounds if the interior temperature rises or falls out of set range |
| Buffered temperature probe | Thermometer probe is encased in a glass bead-filled bottle and stored in a fixed box on the center shelf. This is the ideal way to produce temperature readings closest to stored contents, as recommended by the CDC and VFC's guidelines |

ACR45LSTO Specifications:

| Overview | |
|----------------------------|-----------------------|
| Height of Cabinet | 31.5" (80 cm) |
| Width | 19.5" (50 cm) |
| Depth | 24.75" (63 cm) |
| Depth with Handle | 23.63" (60 cm) |
| Depth with door at 90° | 41.0" (104 cm) |
| Capacity | 2.65 cu.ft. (75 L) |
| Defrost Type | Frost-Free |
| Door | White |
| Cabinet | White |
| US Electrical Safety | ETL |
| Canadian Electrical Safety | ETL-C |
| Amps | 1.0 |
| Voltage/Frequency | 115 V AC/60 Hz |
| Weight | 79.0 lbs. (36 kg) |
| Parts & Labor Warranty | 1 Year |
| Compressor Warranty | 5 Years |
| UPC | 761101076102 |
| Refrigerator Features | |
| Door Swing | RHD |
| Reversible | Factory Reversible |
| Shelf Type | Wire |
| Shelf Qty | 3 |
| Adjustable Shelves | Yes |
| Thermostat Type | Digital |
| Fan Type | Interior and Exterior |
| Refrigerant Type | R600a |
| Refrigerant Amount | 0.99oz. |
| High Side PSI | 270.0 |
| Low Side PSI | 105.0 |
| Level Legs Qty | 4 |
| Interior Light | Yes |
| Temperature Range | 2° to 8°C |
| Dimensions | |
| Interior Height | 21.25" (54 cm) |
| Interior Width | 15.0" (38 cm) |
| Interior Depth | 16.13" (41 cm) |
| Compressor Step Height | 3.5" (9 cm) |

| | |
|-----------------------|---------------|
| Compressor Step Width | 15.0" (38 cm) |
| Compressor Step Depth | 4.75" (12 cm) |

