# accuceld

# ARS32PVBIADA



## Product Features:

#### Purpose-built design Designed and purpose-built for pharmacy, medication, and vaccine applications to support meeting CDC/VFC/VFA guidelines ADA Compliant 32" height is designed to fit under ADA compliant counters Versatile design allows recessed installation under counters or freestanding use Recessed or freestanding use +/-1°C Variation The published temperature variation is derived from the maximum deviation of an NTC sensor in a 1 oz. vial located nearest the chamber geometric center during a 24 hour test period Commercial design Meets UL-471 commercial standards Adjustable temperature Intuitive controls let you adjust the interior temperature between +2°C to +8°C Visual and audible alarms alert if the interior temperature rises or falls out of set range Temperature alarm Remote alarm contacts Electronic controller is equipped with a volt-free contact for alarm forwarding to an external remote system (contacts located in the external rear of the unit) Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup Automatic defrost with adjustable cycle defrost

Performance series Pharma-Vac 2.83 cu.ft. ADA height

solid door commercial all-refrigerator for the display and refrigeration of vaccines; designed for recessed or freestanding installation

32" x 19.75" x 22.63" (H x W x D)

## **Highlights:**

32" height fits under lower ADA compliant counters

Intelligent microprocessor digital temperature controller

Improved temperature accuracy with a separate temperature probe for continuous product readout to simulate stored product temperature

SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

info@summitappliance.com



www.summitappliance.com

# accucold

## **ARS32PVBIADA Specifications:**

Overview	
Nominal Height	32.0" (81 cm)
Height of Cabinet	32.0" (81 cm)
Nominal Width	20.0" (51 cm)
Width	19.75" (50 cm)
Width with Door Open	20.25" (51 cm)
Nominal Depth	23.0" (58 cm)
Depth	22.63" (57 cm)
Depth with Handle	24.38" (62 cm)
Depth with door at 90°	40.0" (102 cm)
Capacity	2.83 cu.ft. (80 L)
Defrost Type	Automatic
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Amps	0.75
Voltage/Frequency	115 V AC/60 Hz
Weight	102.0 lbs. (46 kg)
Parts & Labor Warranty	2 Years
Compressor Warranty	5 Years
UPC	761101075297
Refrigerator Features	
Door Swing	RHD
Reversible	Yes
Shelf Type	Wire
Shelf Qty	4
Adjustable Shelves	Yes
Thermostat Type	Digital
Fan Type	Interior
Refrigerant Type	R600a
Refrigerant Amount	1.41oz.
High Side PSI	280.0
Low Side PSI	90.0
Interior Light	Yes
Temperature Range	2°C to 8°C
Dimensions	
Interior Height	24.0" (61 cm)

Interior Width	16.0" (41 cm)
Interior Depth	15.0" (38 cm)
Compressor Step Height	6.13" (16 cm)
Compressor Step Width	15.25" (39 cm)
Compressor Step Depth	5.5" (14 cm)



