# **FF7BKBISSTBADASR**



#### 32.25" x 23.63" x 23.5" (H x W x D)

ADA compliant built-in undercounter all-refrigerator for general purpose or commercial use, auto defrost w/SS door, removable Speed Rail, towel bar handle, and black cabinet

### **Highlights:**

Commercially approved for use in foodservice establishments

32 inch height fits under lower ADA compliant counters

Speed Rail included for easy storage, display, and access to bar favorites

## **Product Features:**

| ADA compliant  | 32 inch height fits under standard ADA counters   |  |
|--|---|--|
| Commercially approved                                  | ETL-S listed to NSF-7 Standards for use in commercial establishments  |  |
| Slim undercounter dimensions                           | Less than 24 inches wide with a full 5.5 c.f. capacity  |  |
| Built-in capable                                       | Make the best use of space by installing your appliance under the counter and flush with other cabinets   |  |
| Speed Rail included                                    | Made in the USA, the removable SpeedRail allows you to store and display bar essentials on the refrigerator door for easy access by bartenders or waitstaff |  |
| 304 grade stainless steel construction<br>(Speed Rail) | Quality construction built to last  |  |
| Hook-style back (Speed Rail)                           | Designed for easy placement over a door front, while allowing users to remove and reposition as needed  |  |
| Stainless steel wrapped door                           | Durable construction in a professional finish   |  |
| Professional towel bar handle                          | Curved handle in brushed stainless steel offers a sturdy grip with professional elegance  |  |
|  |   |  |

SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

info@summitappliance.com

 $\checkmark$ 





# FF7BKBISSTBADASR Specifications:

| Nominal Height  | 32.0" (81 cm)  |
|---|--|
| Height of Cabinet   | 32.0" (81 cm)  |
| Height to Hinge Cap   | 32.25" (82 cm)   |
| Nominal Width   | 24.0" (61 cm)  |
| Width   | 23.63" (60 cm)   |
| Nominal Depth   | 24.0" (61 cm)  |
| Depth   | 23.5" (60 cm)  |
| Depth with Handle   | 24.75" (63 cm)   |
| Depth with door at 90°  | 45.5" (116 cm)   |
| Capacity  | 5.5 cu.ft. (156 L)   |
| Defrost Type  | Automatic  |
| Door  | Stainless Steel  |
| Cabinet   | Black  |
| US Electrical Safety  | ETL  |
| Canadian Electrical<br>Safety   | ETL-C  |
| Sanitation  | ETL-S  |
| Amps  | 1.4  |
| Voltage/Frequency   | 115 V AC/60 Hz   |
| Weight  | 100.0 lbs. (45 kg)   |
| Parts & Labor Warranty  | 1 Year   |
| Compressor Warranty   | 5 Years  |
| UPC   | 761101081557   |
| <b>Refrigerator Features</b>  |  |
| Door Swing  | RHD  |
| Reversible  | Factory Reversible   |
|   |  |
| Shelf Type  | Glass  |
| Shelf Type<br>Shelf Qty   | Glass<br>3   |
|   |  |
| Shelf Qty   | 3  |
| Shelf Qty<br>Adjustable Shelves   | 3<br>Yes   |
| Shelf Qty<br>Adjustable Shelves<br>Thermostat Type  | 3<br>Yes<br>Dial   |
| Shelf Qty   Adjustable Shelves   Thermostat Type   Refrigerant Type   | 3<br>Yes<br>Dial<br>R600a                                  |
| Shelf QtyAdjustable ShelvesThermostat TypeRefrigerant TypeRefrigerant Amount  | 3<br>Yes<br>Dial<br>R600a<br>0.64oz.                       |
| Shelf QtyAdjustable ShelvesThermostat TypeRefrigerant TypeRefrigerant AmountHigh Side PSI                                     | 3<br>Yes<br>Dial<br>R600a<br>0.64oz.<br>180.0              |
| Shelf Qty<br>Adjustable Shelves<br>Thermostat Type<br>Refrigerant Type<br>Refrigerant Amount<br>High Side PSI<br>Low Side PSI | 3<br>Yes<br>Dial<br>R600a<br>0.64oz.<br>180.0<br>80.0      |
| Shelf QtyAdjustable ShelvesThermostat TypeRefrigerant TypeRefrigerant AmountHigh Side PSILow Side PSILevel Legs Qty           | 3<br>Yes<br>Dial<br>R600a<br>0.64oz.<br>180.0<br>80.0<br>4 |

| Interior Width         | 21.0" (53 cm)  |
|------------------------|----------------|
| Interior Depth         | 17.75" (45 cm) |
| Compressor Step Height | 5.5" (14 cm)   |
| Compressor Step Width  | 21.0" (53 cm)  |
| Compressor Step Depth  | 5.5" (14 cm)   |
|                        |                |



