



# SBC682NK



33.63" x 23.75" x 24.25" (H x W x D)

24" wide, built-in kegerator, approved for commercial, residential, indoor, and outdoor use, with SS cabinet and door, digital controls, and a set of 4 casters

### Highlights:

ETL-S listed to NSF-7 standard and meets UL-471 for use in commercial settings

Meets residential guidelines for home wet bars and similar spaces

Designed for built-in installation under the counter

### Product Features:

|                                    |  |
|------------------------------------|--|
| Large capacity kegerator           | 5.6 cu.ft. interior can accept a full half barrel keg, two slim quarter kegs, or up to three sixth barrel or Cornelius style kegs; compatible with beer, wine, coffee, or nitro coffee tap systems |
| Commercially approved              | ETL-S listed to NSF-7 standard and meets UL-471 for use in commercial settings   |
| Weatherproof design                | Solid 304 grade stainless steel construction allows placement in the outdoors  |
| Built-in capable                   | Front-breathing design allows fully recessed installation under counters   |
| Automatic defrost                  | Reduced user maintenance with auto defrost operation   |
| Digital thermostat                 | Electronic controls ensure easy temperature management, with an external readout in Celsius or Fahrenheit  |
| Tap cool system                    | Keeps cold air flowing to the tower for consistently cold beer   |
| Stainless steel floor cover        | Interior includes steel cover to protect the floor when loading kegs   |
| Top guard rail (ships unassembled) | Attractive chrome guard rail helps to reduce spills and neaten service   |



## SBC682NK Specifications:

| Overview                   |                            |
|----------------------------|----------------------------|
| Height of Cabinet          | 33.63" (85 cm)             |
| Width                      | 23.75" (60 cm)             |
| Depth                      | 24.25" (62 cm)             |
| Depth with Handle          | 26.25" (67 cm)             |
| Depth with door at 90°     | 46.75" (119 cm)            |
| Capacity                   | 5.6 cu.ft. (159 L)         |
| Defrost Type               | Automatic                  |
| Door                       | Stainless Steel            |
| Cabinet                    | Stainless Steel            |
| US Electrical Safety       | ETL                        |
| Canadian Electrical Safety | ETL-C                      |
| Sanitation                 | ETL-S                      |
| Energy Usage/Year          | 305.0kWh/year              |
| Amps                       | 1.25                       |
| Voltage/Frequency          | 115 V AC/60 Hz             |
| Weight                     | 120.0 lbs. (54 kg)         |
| Shipping Weight            | 140.0 lbs. (64 kg)         |
| Parts & Labor Warranty     | 1 Year                     |
| Compressor Warranty        | 5 Years                    |
| UPC                        | 761101075471               |
| Kegeerator                 |                            |
| Door Swing                 | RHD                        |
| Reversible                 | Yes                        |
| Adjustable Shelves         | Yes                        |
| Shelf Type                 | Chrome                     |
| Shelf Qty                  | 2                          |
| Thermostat Type            | Digital                    |
| Fan Type                   | Interior                   |
| Refrigerant                | R600a                      |
| Refrigerant Amount         | 1.06 oz.                   |
| High Side PSI              | 150.0                      |
| Low Side PSI               | 50.0                       |
| Level Legs Qty             | 4                          |
| Wheel Qty                  | 4                          |
| Temperature Range          | 34°F to 68°F (1°C to 20°C) |

Sound Level

