



SBC683OSTRIPLE



33.63" x 23.75" x 24" (H x W x D)

24" wide indoor/outdoor triple tap beer dispenser for built-in or freestanding use in complete stainless steel

Highlights:

Weatherproof construction for safe use in the outdoors

Complete tap kit includes everything you need for the perfect pour

Triple tap system lets you server from three sixtel kegs

Product Features:

| | |
|-----------------------------|---|
| Large capacity kegerator | 5.6 cu.ft. interior can accept a full half barrel or quarter keg, or up to three sixth barrels or Cornelius style kegs |
| Weatherproof design | Solid 304 grade stainless steel construction allows placement in the outdoors |
| Built-in capable | Front-breathing design allows fully recessed installation under counters |
| Complete tap kit | Includes a 5 lb. CO2 tank and regulator, triple tap draft arm, Sankey American tap, and connection hardware |
| Triple tap system | Triple draft tower allows you to serve from three 1/6 (sixel) sized kegs |
| Automatic defrost | Reduced user maintenance with auto defrost operation |
| Digital thermostat | Electronic controls ensure easy temperature management, with an external readout in Celsius or Fahrenheit |
| Tap cool system | Interior tube allows you to extend the cold air flow up into draft tower, ensuring beer freshly tapped stays cold (note: this can be used to cool up to two taps) |
| Stainless steel floor cover | Interior includes steel cover to protect the floor when loading kegs |



SBC683OSTRIPLE Specifications:

| Overview | |
|----------------------------|-----------------------|
| Nominal Height | 34.0" (86 cm) |
| Height of Cabinet | 33.63" (85 cm) |
| Nominal Width | 24.0" (61 cm) |
| Width | 23.75" (60 cm) |
| Nominal Depth | 24.0" (61 cm) |
| Depth | 24.0" (61 cm) |
| Depth with Handle | 26.25" (67 cm) |
| Depth with door at 90° | 46.75" (119 cm) |
| Capacity | 5.6 cu.ft. (159 L) |
| Defrost Type | Automatic |
| Door | Stainless Steel |
| Cabinet | Stainless Steel |
| US Electrical Safety | ETL |
| Canadian Electrical Safety | ETL-C |
| Sanitation | ETL-S |
| Energy Usage/Year | 305.0kWh/year |
| Amps | 1.25 |
| Voltage/Frequency | 115 V AC/60 Hz |
| Weight | 120.0 lbs. (54 kg) |
| Parts & Labor Warranty | 1 Year |
| Compressor Warranty | 5 Years |
| UPC | 761101083940 |
| Kegeerator | |
| Door Swing | RHD |
| Reversible | Yes |
| Tap Kit | Yes |
| Height with Tap | 51.5" (131 cm) |
| Number of Taps | 3 |
| Adjustable Shelves | Yes |
| Shelf Type | Chrome |
| Shelf Qty | 2 |
| Thermostat Type | Digital |
| Fan Type | Interior and Exterior |
| Refrigerant | R600a |
| Refrigerant Amount | 1.06 oz. |

| | |
|-------------------|----------------------------|
| High Side PSI | 150.0 |
| Low Side PSI | 50.0 |
| Inter Height | 26.75" (68 cm) |
| Interior Width | 20.0" (51 cm) |
| Interior Depth | 19.0" (48 cm) |
| Level Legs Qty | 4 |
| Wheel Qty | 4 |
| Temperature Range | 34°F to 68°F (1°C to 20°C) |
| Sound Level | 34.0 db |

