



SBC682CMTWIN



33.63" x 23.75" x 24.25" (H x W x D)

24" wide indoor/outdoor dual tap combination cold brew/nitro coffee dispenser for built-in or freestanding commercial or residential use, with stainless steel exterior and caster set

Highlights:

Commercially approved to NSF-7 standards

Unique tap combination allows you to serve both nitro and regular cold brew on tap from two separate sixtel kegs

Weatherproof construction for safe use in the outdoors

Product Features:

| | |
|--------------------------------------|---|
| Dispenses both flat and nitro coffee | Unique combination stout and standard tap system allows you to serve both flat iced cold brew and nitro drafts |
| Full-sized dispenser | 5.6 cu.ft. interior can accept a full half barrel or quarter keg, or up to three sixth barrels or Cornelius style kegs |
| Commercially approved | ETL-S listed to NSF-7 standards and meets UL-471 for use in commercial settings |
| Weatherproof design | Solid 304 grade stainless steel construction allows placement in the outdoors |
| Built-in capable | Front-breathing design allows fully recessed installation under counters |
| Complete dual tap kit | Commercial grade tap kit includes a dual tap draft tower with a standard and stout tap, Nitrogen tank, dual gauge regulator, and connections for ball lock Cornelius kegs |
| Dual tap system | Twin draft tower allows you to serve from two 1/6 (sixel) sized kegs |
| Automatic defrost | Reduced user maintenance with auto defrost operation |
| Digital thermostat | Electronic controls ensure easy temperature management, with an external readout in Celsius or Fahrenheit |



SBC682CMTWIN Specifications:

| Overview | |
|----------------------------|-----------------------|
| Height of Cabinet | 33.63" (85 cm) |
| Width | 23.75" (60 cm) |
| Depth | 24.25" (62 cm) |
| Depth with Handle | 26.25" (67 cm) |
| Depth with door at 90° | 46.75" (119 cm) |
| Capacity | 5.6 cu.ft. (159 L) |
| Defrost Type | Automatic |
| Door | Stainless Steel |
| Cabinet | Stainless Steel |
| US Electrical Safety | ETL |
| Canadian Electrical Safety | ETL-C |
| Sanitation | ETL-S |
| Energy Usage/Year | 305.0kWh/year |
| Amps | 1.25 |
| Voltage/Frequency | 115 V AC/60 Hz |
| Weight | 120.0 lbs. (54 kg) |
| Shipping Weight | 156.0 lbs. (71 kg) |
| Parts & Labor Warranty | 1 Year |
| Compressor Warranty | 5 Years |
| UPC | 761101084015 |
| Kegeerator | |
| Door Swing | RHD |
| Reversible | Yes |
| Tap Kit | Yes |
| Height with Tap | 51.5" (131 cm) |
| Number of Taps | 2 |
| Adjustable Shelves | Yes |
| Shelf Type | Chrome |
| Shelf Qty | 2 |
| Thermostat Type | Digital |
| Fan Type | Interior and Exterior |
| Refrigerant | R600a |
| Refrigerant Amount | 1.06 oz. |
| High Side PSI | 150.0 |
| Low Side PSI | 50.0 |

| | |
|-------------------|----------------------------|
| Inter Height | 26.75" (68 cm) |
| Interior Width | 20.0" (51 cm) |
| Interior Depth | 19.0" (48 cm) |
| Level Legs Qty | 4 |
| Wheel Qty | 4 |
| Temperature Range | 34°F to 68°F (1°C to 20°C) |
| Sound Level | 34.0 db |

