

SCFM203



32.63" x 76" x 28.25" (H x W x D)

Commercially listed 19.8 cu.ft. manual defrost chest freezer in white with stainless steel corner guards and lock

Highlights:

Commercially approved for use in foodservice establishments

19.8 cu.ft. interior for large capacity storage

Manual defrost operation and static cooling system

Product Features:

Large capacity	19.8 cu.ft. of interior storage
Commercially approved	ETL-S listed to ANSI-NSF Standard 7 for commercial use
Factory installed lock	Keyed lock for a secure interior (2 keys included)
Manual defrost operation	Static cooling system with a rear-mounted drain for easier defrosting as needed
Counterbalanced hinges	The lid will remain open once lifted for safer loading
Thick insulation	3 1/2" thick walls ensure proper insulation for reliable storage
Stainless steel front corner protectors	External "bumpers" included for easy installation to help protect the corners in high traffic environments
Hammered aluminum interior	Solid construction for durable storage in busy settings
Easy-grip handle	External handle for easy opening

SCFM203 Specifications:

Overview	
Nominal Height	33.0" (84 cm)
Height of Cabinet	32.63" (83 cm)
Nominal Width	76.0" (193 cm)
Width	76.0" (193 cm)
Nominal Depth	29.0" (74 cm)
Depth	28.25" (72 cm)
Depth with Handle	30.0" (76 cm)
Capacity	19.8 cu.ft. (561 L)
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Amps	3.6
Voltage/Frequency	115 V AC/60 Hz
Weight	205.0 lbs. (93 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101080802
Freezer	
Door Swing	Lift-Up
Interior Height	24.25" (62 cm)
Interior Width	70.25" (178 cm)
Interior Depth	20.75" (53 cm)
Thermostat Type	Dial
Refrigerant Type	R290
Refrigerant Amount	3.03 oz.
High Side PSI	400.0
Low Side PSI	200.0
Wheels	6
Compressor Step Height	10.25" (26 cm)
Compressor Step Width	11.75" (30 cm)
Compressor Step Depth	20.75" (53 cm)
Temperature Range	-10 to -26°C

