

SCFM103



33.25" x 44" x 25.5" (H x W x D)

Commercially listed 10 cu.ft. manual defrost chest freezer in white with stainless steel corner guards and lock

Highlights:

Commercially approved for use in foodservice establishments

10 cu.ft. interior for large capacity storage

Manual defrost operation and static cooling system

Product Features:

Large capacity	10 cu.ft. of interior storage
Commercially approved	ETL-S listed to ANSI-NSF Standard 7 for commercial use
Lock included	Ships with a keyed lock and two keys for optional installation on the lid
Manual defrost operation	Static cooling system with a front drain for easier defrosting as needed
Counterbalanced hinges	The lid will remain open once lifted for easier loading
Thick insulation	3 1/2" thick walls ensure proper insulation for reliable storage
Stainless steel front corner protectors	Factory-installed external "bumpers" to help protect the corners in busy high traffic environments
Hammered aluminum interior	Solid construction for durable storage in busy settings
Easy-grip handle	External handle for easy opening (ships unsassembled)





SCFM103 Specifications:

Defrost Type Door Cabinet US Electrical Safety Canadian Electrical Safety Sanitation Amps Voltage/Frequency	34.0" (86 cm) 33.25" (84 cm) 44.0" (112 cm) 44.0" (112 cm) 26.0" (66 cm) 25.5" (65 cm) 27.25" (69 cm) 10.0 cu.ft. (283 L) Manual White ETL ETL-C
Nominal Width Width Nominal Depth Depth Depth with Handle Capacity Defrost Type Door Cabinet US Electrical Safety Canadian Electrical Safety Sanitation Amps Voltage/Frequency	44.0" (112 cm) 44.0" (112 cm) 26.0" (66 cm) 25.5" (65 cm) 27.25" (69 cm) 10.0 cu.ft. (283 L) Manual White ETL ETL-C
WidthNominal DepthDepthDepth with HandleCapacityCapacityDefrost TypeDoorCabinetUS Electrical SafetyCanadian Electrical SafetySanitationAmpsVoltage/Frequency	44.0" (112 cm) 26.0" (66 cm) 25.5" (65 cm) 27.25" (69 cm) 10.0 cu.ft. (283 L) Manual White ETL ETL ETL-C
Nominal DepthDepthDepth with HandleCapacityDefrost TypeDoorCabinetUS Electrical SafetyCanadian Electrical SafetySanitationAmpsVoltage/Frequency	26.0" (66 cm) 25.5" (65 cm) 27.25" (69 cm) 10.0 cu.ft. (283 L) Manual White White ETL ETL-C
Depth Depth with Handle Capacity Defrost Type Door Cabinet US Electrical Safety Canadian Electrical Safety Sanitation Amps Voltage/Frequency	25.5" (65 cm) 27.25" (69 cm) 10.0 cu.ft. (283 L) Manual White White ETL ETL-C
Depth with Handle Capacity Defrost Type Door Cabinet US Electrical Safety Canadian Electrical Safety Sanitation Amps Voltage/Frequency	27.25" (69 cm) 10.0 cu.ft. (283 L) Manual White White ETL ETL-C
Capacity Capacity Capacity Cabinet US Electrical Safety Canadian Electrical Safety Sanitation Amps Voltage/Frequency	10.0 cu.ft. (283 L) Manual White White ETL ETL-C
Defrost Type Door Cabinet US Electrical Safety Canadian Electrical Safety Sanitation Amps Voltage/Frequency	Manual White White ETL ETL-C
Door Cabinet US Electrical Safety Canadian Electrical Safety Sanitation Amps Voltage/Frequency	White White ETL ETL-C
Cabinet US Electrical Safety Canadian Electrical Safety Sanitation Amps Voltage/Frequency	White ETL ETL-C
US Electrical Safety Canadian Electrical Safety Sanitation Amps Voltage/Frequency	ETL ETL-C
Canadian Electrical Safety Sanitation Amps Voltage/Frequency	ETL-C
Safety Sanitation Amps Voltage/Frequency	
Amps Voltage/Frequency	
Voltage/Frequency	ETL-S
	2.47
Woight	115 V AC/60 Hz
Weight	120.0 lbs. (54 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101080826
Freezer	
Door Swing	Lift-Up
Interior Height	26.0" (66 cm)
Interior Width	38.0" (97 cm)
Interior Depth	18.0" (46 cm)
Thermostat Type	Dial
Refrigerant Type	R600a
Refrigerant Amount	2.2 oz.
High Side PSI	300.0
Low Side PSI	130.0
Wheels	4
Compressor Step Height	8.75" (22 cm)
Compressor Step Width	7.75" (20 cm)
Compressor Step Depth	
Temperature Range	18.0" (46 cm)



