SUMMIT

SINC2B230B



1.88" x 11.38" x 20.5" (H x W x D)

ENERGY STAR certified 3600W 208-240V 12" wide 2-zone built-in induction cooktop with a jet black glass surface, touch controls, and power boost

Highlights:

3600W of cooking power with boost functions for both elements

Advanced safety features include automatic shutoff, overflow protection, child lock, and residual heat indicator light

Jet black glass surface offers a modern look that's easy to clean

Product Features:

Smooth-top glass cooktop ideal for hotels, apartments, and other small kitchen spaces
Rated by the DOE to perform with more efficiency than federal standards require, saving your unit energy and you on higher utility costs
Electromagnetic heating technology where heat is generated inside your cookware, ensuring a more efficient process with less energy waste, faster heating, and a safer cooking experience
Powerful elements with fast heating to meet most stovetop cooking needs
Elegant style on a smooth, jet blaack glass surface for a contemporary look that is easier to clean
8 1/4" element operates at 2000W (with a 2600W capacity at the boost setting) for fast, powerful heating
6 1/4" front element operates at 1500W (or 2000W using boost) to cover most general cooking needs
Both cooking zones include a "boost" function that lets them operate at a higher setting for up to 5 minutes, ideal for reducing cook time when boiling water

SUMMINITURACIONANCE DIVISION, FELIX STORCH, Allows 150 programe aither burner to heat at a specified level for up to 99 minutes and either 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893 μετροφίτων βυτικόν στο displace αυτοφονιστική τη προσκή προσκη του μετροφονιστική του του 1049 μετροφονία μετροφονί



SINC2B230B Specifications:

Nominal Height 1.88" (5 of Height of Cabinet 1.88" (5 of Nominal Width 12.0" (30 of Nominal Width 14.30" (30 of Nominal Width 14.30" (30 of Nominal Width)	cm)
Nominal Width 12.0" (30 d	,
,	cm)
\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	cm)
Width 11.38" (29 c	cm)
Nominal Depth 21.0" (53 c	cm)
Depth 20.5" (52 d	cm)
Cabinet Bl	ack
US Electrical Safety E	ΞTL
Canadian Electrical Safety ET	L-C
Amps 1	5.0
Voltage/Frequency 240 V AC/60	Hz
Weight 14.0 lbs. (6	kg)
Parts & Labor Warranty 1 Y	⁄ear
UPC 7611010838	520
Industry Oscillan	
Induction Cooktop	
Application Buil	lt-in
-	
Application Built Heating Type Induct	
Application Buil Heating Type Induct	tion
Application Built Heating Type Induct Surface GI Number of Elements	tion ass
Application Built Heating Type Induct Surface Gl Number of Elements Controls Dig	tion ass 2
Application Built Heating Type Induct Surface Gl Number of Elements Controls Dig	tion ass 2 gital Yes
Application Built Heating Type Induct Surface GI Number of Elements Controls Dig Cooking Timer	tion ass 2 gital Yes cm)
Application Built Heating Type Induct Surface Gl Number of Elements Controls Dig Cooking Timer Countertop Cutout Width 10.63" (27 of	tion ass 2 gital Yes cm)
Application Built Heating Type Induct Surface GI Number of Elements Controls Dig Cooking Timer Countertop Cutout Width 10.63" (27 of the countertop Cutout Depth 19.63" (50 of the countertop Cutout D	tion ass 2 gital Yes cm)
Application Built Heating Type Induct Surface GI Number of Elements Controls Dig Cooking Timer Countertop Cutout Width 10.63" (27 of the countertop Cutout Depth 19.63" (50 of the countertop Cutout D	tion ass 2 gital Yes cm) ccm) 40V
Application Built Heating Type Induct Surface Gl. Number of Elements Controls Dig Cooking Timer Countertop Cutout Width 10.63" (27 of the countertop Cutout Depth 19.63" (50 of the countertop Cutout	tion ass 2 gital Yes cm) ccm) 40V
Application Built Heating Type Induct Surface Gl. Number of Elements Controls Dig Cooking Timer Countertop Cutout Width 10.63" (27 of the countertop Cutout Depth 19.63" (50 of the countertop Cutout	ass 2 gital Yes cm) cm) 3.25



