

SCFM133



32.75" x 50.25" x 29.25" (H x W x D)

Commercially listed 12.1 cu.ft. manual defrost chest freezer in white with stainless steel corner guards and lock

Highlights:

Commercially approved for use in foodservice establishments

12.1 cu.ft. interior for large capacity storage

Manual defrost operation and static cooling system

Product Features:

Large capacity	Over 12 cu.ft. of interior storage
Commercially approved	ETL-S listed to ANSI-NSF Standard 7 for commercial use
Lock included	Ships with a keyed lock and two keys for optional installation on the lid
Manual defrost operation	Static cooling system with a front drain for easier defrosting as needed
Counterbalanced hinges	The lid will remain open once lifted for easier loading
Thick insulation	3 1/2" thick walls ensure proper insulation for reliable storage
Stainless steel front corner protectors	Factory-installed external "bumpers" to help protect the corners in busy high traffic environments
Hammered aluminum interior	Solid construction for durable storage in busy settings
Easy-grip handle	External handle for easy opening (ships unassembled)



SCFM133 Specifications:

Overview	
Height of Cabinet	32.75" (83 cm)
Width	50.25" (128 cm)
Depth	29.25" (74 cm)
Depth with Handle	31.0" (79 cm)
Capacity	12.1 cu.ft. (343 L)
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Amps	2.8
Voltage/Frequency	115 V AC/60 Hz
Shipping Weight	140.0 lbs. (64 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101081625
Freezer	
Door Swing	Lift-Up
Interior Height	24.0" (61 cm)
Interior Width	44.0" (112 cm)
Interior Depth	21.5" (55 cm)
Thermostat Type	Dial
Refrigerant Type	R290a
Refrigerant Amount	2.65 oz.
High Side PSI	400.0
Low Side PSI	200.0
Wheels	2
Compressor Step Height	9.5" (24 cm)
Compressor Step Width	11.75" (30 cm)
Compressor Step Depth	21.5" (55 cm)
Temperature Range	-10 to -26°C

