## accuc@ld

# **VT73**



33.25" x 37.5" x 22.25" (H x W x D)

-30°C laboratory 6.7 cu.ft. chest freezer with stainless steel corner guards, NIST calibrated thermometer with alarm, and lock

#### **Highlights:**

Designed to operate at -30°C for select laboratory, pharmacy, industrial, and other institutional storage needs

Includes an external NIST calibrated readout of the current and high/low temperature with an audible alarm

Manual defrost operation and static cooling system

#### **Product Features:**

| Low temperature chest freezer       | Operates at -30°C for use in laboratories, research facilities, and other settings with lower temperature cold storage needs  |
|-------------------------------------|---|
| NIST calibrated temperature display | Alarm includes continuous NIST calibrated display of the current interior and high/low temperature, and can be switched from Celsius to Fahrenheit at the touch of a button   |
| High/low temperature alarm          | Audible alarm sounds if the interior temperature rises or falls out of set range  |
| Certificate of calibration          | 2-year certificate included for your records  |
| Buffered temperature probe          | Thermometer probe is encased in a glycol-filled bottle and stored in a fixed box on the center shelf. This is the ideal way to produce temperature readings closest to stored contents, as recommended by the CDC, VFC and VFA's guidelines |
| Factory-installed lock              | Added security with a locking lid (2 keys included)   |
| Manual defrost operation            | Static cooling system with a front drain for easier defrosting as needed  |
| Digital controls                    | Externally located digital thermostat allows you to adjust the temperature as needed without opening the lid  |
| Counterbalanced hinges              | The lid will remain open once lifted for easier loading   |

## accuc@ld

### **VT73 Specifications:**

| Overview                      |                    |
|-------------------------------|--------------------|
| Nominal Height                | 34.0" (86 cm)      |
| Height of Cabinet             | 33.25" (84 cm)     |
| Nominal Width                 | 38.0" (97 cm)      |
| Width                         | 37.5" (95 cm)      |
| Nominal Depth                 | 23.0" (58 cm)      |
| Depth                         | 22.25" (57 cm)     |
| Depth with Handle             | 24.0" (61 cm)      |
| Capacity                      | 6.7 cu.ft. (190 L) |
| Defrost Type                  | Manual             |
| Door                          | White              |
| Cabinet                       | White              |
| US Electrical Safety          | ETL                |
| Canadian Electrical Safety    | ETL-C              |
| Sanitation                    | ETL-S              |
| Amps                          | 1.4                |
| Voltage/Frequency             | 115 V AC/60 Hz     |
| Parts & Labor Warranty        | 1 Year             |
| Compressor Warranty           | 5 Years            |
| UPC                           | 761101086347       |
| Freezer                       |                    |
| Door Swing                    | Lift-Up            |
| Interior Height               | 26.0" (66 cm)      |
| Interior Width                | 32.0" (81 cm)      |
| Interior Depth                | 15.0" (38 cm)      |
| Thermostat Type               | Digital            |
| Refrigerant Type              | R600a              |
| Refrigerant Amount            | 1.76 oz.           |
| -                             |                    |
| High Side PSI                 | 300.0              |
| High Side PSI<br>Low Side PSI | 300.0<br>130.0     |
|                               |                    |
| Low Side PSI                  | 130.0              |

