accucold

VT133



32.75" x 50.25" x 29.25" (H x W x D)

-30°C laboratory 12.1 cu.ft. chest freezer with stainless steel corner guards, NIST calibrated thermometer with alarm, and lock

Highlights:

Designed to operate at -30°C for select laboratory, pharmacy, industrial, and other institutional storage needs

Includes an external NIST calibrated readout of the current and high/low temperature with an audible alarm

Manual defrost operation and static cooling system

Product Features:

Low temperature chest freezer	Operates at -30°C for use in laboratories, research facilities, and other settings with lower temperature cold storage needs
NIST calibrated temperature display	Alarm includes continuous NIST calibrated display of the current interior and high/low temperature, and can be switched from Celsius to Fahrenheit at the touch of a button
High/low temperature alarm	Audible alarm sounds if the interior temperature rises or falls out of set range
Certificate of calibration	2-year certificate included for your records
Buffered temperature probe	Thermometer probe is encased in a glycol-filled bottle and stored in a fixed box on the center shelf. This is the ideal way to produce temperature readings closest to stored contents, as recommended by the CDC, VFC and VFA's guidelines
Factory-installed lock	Added security with a locking lid (2 keys included)
Manual defrost operation	Static cooling system with a front drain for easier defrosting as needed
Digital controls	Externally located digital thermostat allows you to adjust the temperature as needed without opening the lid
Counterbalanced hinges	The lid will remain open once lifted for easier loading

SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

info@summitappliance.com



accuceld

VT133 Specifications:

Nominal Height33.0" (84 cm)Height of Cabinet32.75" (83 cm)Nominal Width51.0" (130 cm)Width50.25" (128 cm)Nominal Depth30.0" (76 cm)Depth29.25" (74 cm)Depth with Handle31.0" (79 cm)Capacity12.1 cu.ft. (343 L)Defrost TypeManualDoorWhiteCabinetWhiteUS Electrical SafetyETL-CSanitationETL-SAmps2.8Voltage/Frequency115 V AC/60 HzWeight130.0 lbs. (59 kg)Parts & Labor Warranty1 YearCompressor Warranty5 YearsUPC761101086361
Nominal Width51.0" (130 cm)Width50.25" (128 cm)Nominal Depth30.0" (76 cm)Depth29.25" (74 cm)Depth with Handle31.0" (79 cm)Capacity12.1 cu.ft. (343 L)Defrost TypeManualDoorWhiteCabinetWhiteUS Electrical SafetyETL-CSanitationETL-SAmps2.8Voltage/Frequency115 V AC/60 HzWeight130.0 lbs. (59 kg)Parts & Labor Warranty1 YearCompressor Warranty5 Years
Width50.25" (128 cm)Nominal Depth30.0" (76 cm)Depth29.25" (74 cm)Depth with Handle31.0" (79 cm)Capacity12.1 cu.ft. (343 L)Defrost TypeManualDoorWhiteCabinetWhiteUS Electrical SafetyETLCanadian ElectricalETL-CSafetySanitationVoltage/Frequency115 V AC/60 HzWeight130.0 lbs. (59 kg)Parts & Labor Warranty1 YearCompressor Warranty5 Years
Nominal Depth30.0" (76 cm)Depth29.25" (74 cm)Depth with Handle31.0" (79 cm)Capacity12.1 cu.ft. (343 L)Defrost TypeManualDoorWhiteCabinetWhiteUS Electrical SafetyETLCanadian ElectricalETL-CSafetySanitationETL-SAmpsVoltage/Frequency115 V AC/60 HzWeight130.0 lbs. (59 kg)Parts & Labor Warranty1 YearCompressor Warranty5 Years
Depth29.25" (74 cm)Depth with Handle31.0" (79 cm)Capacity12.1 cu.ft. (343 L)Defrost TypeManualDoorWhiteCabinetWhiteUS Electrical SafetyETLCanadian ElectricalETL-CSafetySanitationSanitationETL-SAmps2.8Voltage/Frequency115 V AC/60 HzWeight130.0 lbs. (59 kg)Parts & Labor Warranty1 YearCompressor Warranty5 Years
Depth with Handle31.0" (79 cm)Capacity12.1 cu.ft. (343 L)Defrost TypeManualDoorWhiteCabinetWhiteUS Electrical SafetyETLCanadian ElectricalETL-CSafetySanitationSanitationETL-SAmps2.8Voltage/Frequency115 V AC/60 HzWeight130.0 lbs. (59 kg)Parts & Labor Warranty1 YearCompressor Warranty5 Years
Capacity12.1 cu.ft. (343 L)Defrost TypeManualDoorWhiteCabinetWhiteUS Electrical SafetyETL-CCanadian ElectricalETL-CSafetySanitationSanitationETL-SAmps2.8Voltage/Frequency115 V AC/60 HzWeight130.0 lbs. (59 kg)Parts & Labor Warranty1 YearCompressor Warranty5 Years
Defrost TypeManualDoorWhiteCabinetWhiteUS Electrical SafetyETLCanadian ElectricalETL-CSafetySanitationSanitationETL-SAmps2.8Voltage/Frequency115 V AC/60 HzWeight130.0 lbs. (59 kg)Parts & Labor Warranty1 YearCompressor Warranty5 Years
DoorWhiteCabinetWhiteUS Electrical SafetyETLCanadian ElectricalETL-CSafetySanitationSanitationETL-SAmps2.8Voltage/Frequency115 V AC/60 HzWeight130.0 lbs. (59 kg)Parts & Labor Warranty1 YearCompressor Warranty5 Years
CabinetWhiteUS Electrical SafetyETLCanadian ElectricalETL-CSafetySanitationSanitationETL-SAmps2.8Voltage/Frequency115 V AC/60 HzWeight130.0 lbs. (59 kg)Parts & Labor Warranty1 YearCompressor Warranty5 Years
US Electrical SafetyETLCanadian Electrical SafetyETL-CSanitationETL-SAmps2.8Voltage/Frequency115 V AC/60 HzWeight130.0 lbs. (59 kg)Parts & Labor Warranty1 YearCompressor Warranty5 Years
Canadian Electrical SafetyETL-CSanitationETL-SAmps2.8Voltage/Frequency115 V AC/60 HzWeight130.0 lbs. (59 kg)Parts & Labor Warranty1 YearCompressor Warranty5 Years
SafetySanitationAmps2.8Voltage/Frequency115 V AC/60 HzWeight130.0 lbs. (59 kg)Parts & Labor Warranty1 YearCompressor Warranty5 Years
Amps2.8Voltage/Frequency115 V AC/60 HzWeight130.0 lbs. (59 kg)Parts & Labor Warranty1 YearCompressor Warranty5 Years
Voltage/Frequency115 V AC/60 HzWeight130.0 lbs. (59 kg)Parts & Labor Warranty1 YearCompressor Warranty5 Years
Weight130.0 lbs. (59 kg)Parts & Labor Warranty1 YearCompressor Warranty5 Years
Parts & Labor Warranty 1 Year Compressor Warranty 5 Years
Compressor Warranty 5 Years
i
UPC 761101086361
Freezer
Door Swing Lift-Up
Interior Height 24.0" (61 cm)
Interior Width 44.0" (112 cm)
Interior Depth 21.5" (55 cm)
Thermostat Type Digital
Refrigerant Type R290
Refrigerant Amount 2.65 oz.
High Side PSI 400.0
Low Side PSI 200.0
Wheels 2
Compressor Step Height 9.5" (24 cm)
Compressor Step Width 11.75" (30 cm)



