## accuc@ld

# **VT252**



36.75" x 91.25" x 28.25" (H x W x D)

-30°C laboratory 26.7 cu.ft. chest freezer with stainless steel corner guards, NIST calibrated thermometer with alarm, and lock

### **Highlights:**

Designed to operate at -30°C for select laboratory, pharmacy, industrial, and other institutional storage needs

Includes an external NIST calibrated readout of the current and high/low temperature with an audible alarm

Manual defrost operation and static cooling system

#### **Product Features:**

Low temperature chest freezer	Operates at -30°C for use in laboratories, research facilities, and other settings with lower temperature cold storage needs
NIST calibrated temperature display	Alarm includes continuous NIST calibrated display of the current interior and high/low temperature, and can be switched from Celsius to Fahrenheit at the touch of a button
High/low temperature alarm	Audible alarm sounds if the interior temperature rises or falls out of set range
Certificate of calibration	2-year certificate included for your records
Buffered temperature probe	Thermometer probe is encased in a glycol-filled bottle and stored in a fixed box on the center shelf. This is the ideal way to produce temperature readings closest to stored contents, as recommended by the CDC, VFC and VFA's guidelines
Factory-installed lock	Added security with a locking lid (2 keys included)
Manual defrost operation	Static cooling system with a front drain for easier defrosting as needed
Digital controls	Externally located digital thermostat allows you to adjust the temperature as needed without opening the lid
Counterbalanced hinges	The lid will remain open once lifted for easier loading

## accuc@ld

### **VT252 Specifications:**

Overview	
Height of Cabinet	36.75" (93 cm)
Width	91.25" (232 cm)
Depth	28.25" (72 cm)
Depth with Handle	30.0" (76 cm)
Capacity	26.66 cu.ft. (755 L)
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Amps	2.3
Voltage/Frequency	115 V AC/60 Hz
Weight	250.0 lbs. (113 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101086392
Freezer	
Door Swing	Lift-Up
Interior Height	27.5" (70 cm)
Interior Width	85.5" (217 cm)
Interior Width Interior Depth	85.5" (217 cm) 20.75" (53 cm)
Interior Depth	20.75" (53 cm)
Interior Depth Thermostat Type	20.75" (53 cm)  Digital
Interior Depth Thermostat Type Refrigerant Type	20.75" (53 cm)  Digital  R290
Interior Depth Thermostat Type Refrigerant Type Refrigerant Amount	20.75" (53 cm)  Digital  R290  3.39 oz.
Interior Depth Thermostat Type Refrigerant Type Refrigerant Amount High Side PSI	20.75" (53 cm)  Digital  R290  3.39 oz.  246.0
Interior Depth Thermostat Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI	20.75" (53 cm)  Digital  R290  3.39 oz.  246.0  132.0
Interior Depth Thermostat Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI Wheels	20.75" (53 cm)  Digital  R290  3.39 oz.  246.0  132.0



