



# ADRD241CSS



31.88" x 23.38" x 22.5" (H x W x D)

24 in. wide ADA compliant 2-drawer all-refrigerator for indoor or outdoor residential or commercial use, stainless steel exterior with panel-ready drawer fronts

**Highlights:**

32" height for use under lower ADA compliant counters

Panel-ready drawers allow you to customize the look to match existing cabinetry

Complete stainless steel construction inside and out

**Product Features:**

2-Drawer All-Refrigerator	24" wide 3.7 cu.ft. all-refrigerator with two gliding drawers
ADA compliant design	Sized just under 32" high to allow installation under lower ADA compliant counters
Built-in capable	Front-breathing design allows you to make the best use of space by installing your appliance under the counter and flush with other cabinets in 24" wide openings
Indoor/Outdoor compatible	Constructed and approved for outdoor installation (as well as use indoors) with a fully sealed cooling system and weatherproof exterior
Stainless steel drawers	Drawer interiors and exteriors are fully constructed from 304 grade stainless steel for weatherproof durability and elegant style
Panel-ready drawer fronts	Drawers accept overlay panels (size: 23.43" x 14.1" at 3/4" thick) to let you seamlessly blend the refrigerator into cabinetry design
Professional handles	Sleek stainless steel handles add an elegant touch to any setting
Frost-free	No-frost operation for minimum user maintenance
Digital thermostat	Electronic controls located on the top drawer ensure intuitive temperature management, with an external readout that can switch from Celsius to Fahrenheit at the touch of a button



## ADRD241CSS Specifications:

### Overview

Nominal Height	32.0" (81 cm)
Height of Cabinet	31.88" (81 cm)
Nominal Width	24.0" (61 cm)
Width	23.38" (59 cm)
Nominal Depth	23.0" (58 cm)
Depth	22.5" (57 cm)
Depth with Handle	23.88" (61 cm)
Depth with door at 90°	34.25" (87 cm)
Capacity	3.7 cu.ft. (105 L)
Defrost Type	Frost-Free
Door	Stainless Steel/Panel-Ready
Cabinet	Stainless Steel
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Energy Usage/Year	185.0kWh/year
Amps	1.0
Voltage/Frequency	115 V AC/60 Hz
Weight	136.0 lbs. (62 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101088228

### Refrigerator Features

Sabbath Mode	Yes
Door Swing	Drawer
Thermostat Type	Digital
Fan Type	Interior and Exterior
Refrigerant Type	R600a
Refrigerant Amount	1.38oz.
High Side PSI	270.0
Low Side PSI	105.0
Level Legs Qty	4
Interior Light	Yes
Temperature Range	36 to 43°F
Sound Level	33 dB

### Drawer Dimensions

Interior Height 1	8.0" (20 cm)
Interior Width 1	17.0" (43 cm)
Interior Depth 1	14.5" (37 cm)
Interior Height 2	8.0" (20 cm)
Interior Width 2	17.0" (43 cm)
Interior Depth 2	14.5" (37 cm)

### Dimensions

Compressor Step Height	4.0" (10 cm)
Compressor Step Width	17.0" (43 cm)
Compressor Step Depth	3.5" (9 cm)

