



# ASDS1523



32" x 14.75" x 17.75" (H x W x D)

15" wide shallow depth built-in undercounter ADA compliant all-refrigerator with stainless steel door and interior, black cabinet, lock, and digital controls

### Highlights:

Uniquely shallow depth under 18" for an easy fit in kitchen islands

Flexible design allows for built-in or freestanding use in 15 inch wide spaces

32" height for use under lower ADA compliant counters

### Product Features:

|                           |  |
|---------------------------|--|
| 15" wide all-refrigerator | 1.7 cu.ft. interior for residential or commercial cold storage   |
| Less than 18" deep        | Unique 17.75" shallow depth is ideal for wet bars, island kitchens, and other undercounter areas with limited footprint space  |
| ADA compliant design      | 32" height allows easy installation under lower ADA compliant counters   |
| Adjustable height         | Leveling legs can be extended up to 2", with a slide-out kickplate that allows you to raise the overall height from 32" up to 34" if used under more standard sized cabinets |
| Built-in capable          | Front-breathing design lets you make the best use of space by installing your appliance under the counter  |
| Stainless steel interior  | Walls and floor are constructed from stainless steel for added strength and easy cleanup   |
| Stainless steel door      | Durable construction with a professional look  |
| Factory-installed lock    | Keyed lock for a secure interior (2 keys included)   |
| Professional handle       | Includes a full-length pro handle in chrome  |



## ASDS1523 Specifications:

| Overview                   |                       |
|----------------------------|-----------------------|
| Height of Cabinet          | 32.0" (81 cm)         |
| Width                      | 14.75" (37 cm)        |
| Depth                      | 17.75" (45 cm)        |
| Depth with Handle          | 19.75" (50 cm)        |
| Depth with door at 90°     | 31.25" (79 cm)        |
| Capacity                   | 1.72 cu.ft. (49 L)    |
| Defrost Type               | Frost-Free            |
| Door                       | Stainless Steel       |
| Cabinet                    | Black                 |
| US Electrical Safety       | ETL                   |
| Canadian Electrical Safety | ETL-C                 |
| Sanitation                 | ETL-S                 |
| Energy Usage/Year          | 235.0kWh/year         |
| Amps                       | 1.0                   |
| Voltage/Frequency          | 115 V AC/60 Hz        |
| Weight                     | 59.0 lbs. (27 kg)     |
| Shipping Weight            | 70.0 lbs. (32 kg)     |
| Parts & Labor Warranty     | 1 Year                |
| Compressor Warranty        | 5 Years               |
| UPC                        | 761101079523          |
| Refrigerator Features      |                       |
| Sabbath Mode               | Yes                   |
| Door Swing                 | Reversible            |
| Reversible                 | Yes                   |
| Height Adjustable          | Yes                   |
| Shelf Type                 | Glass                 |
| Shelf Qty                  | 3                     |
| Adjustable Shelves         | Yes                   |
| Thermostat Type            | Digital               |
| Fan Type                   | Interior and Exterior |
| Refrigerant Type           | R600a                 |
| Refrigerant Amount         | 0.64oz.               |
| High Side PSI              | 270.0                 |
| Low Side PSI               | 105.0                 |
| Level Legs Qty             | 4                     |
| Interior Light             | Yes                   |
| Temperature Range          | 36 to 43°F            |

Sound Level 33 dB

| Dimensions             |                |
|------------------------|----------------|
| Interior Height        | 24.25" (62 cm) |
| Interior Width         | 10.75" (27 cm) |
| Interior Depth         | 12.38" (31 cm) |
| Compressor Step Height | 3.75" (10 cm)  |
| Compressor Step Width  | 10.75" (27 cm) |
| Compressor Step Depth  | 5.5" (14 cm)   |

