SUMMIT

ASDR2414PNR



32" x 23.38" x 17.88" (H x W x D)

24" wide hallow depth built-in undercounter ADA compliant 2-drawer refrigerator with panel-ready stainless steel drawer fronts and black cabinet

Highlights:

Uniquely shallow depth under 18" for an easy fit in kitchen islands

Panel-ready drawers allow you to customize the look to match existing cabinetry

32" height for use under lower ADA compliant counters

Product Features:


2-Drawer All-Refrigerator	24" wide 3.1 cu.ft. all-refrigerator with two gliding drawers	
Panel-ready drawer fronts	Drawers accept overlay panels (size: 23.43" x 14.1" at 3/4" thick) to let you seamlessly blend the refrigerator into cabinetry design	
Less than 18" deep	Unique 17.88" shallow depth is ideal for wet bars, island kitchens, and other undercounter areas with limited footprint space	
ADA compliant design	Sized just under 32" high to allow installation under lower ADA compliant counters	
Adjustable height	Leveling legs can be extended up to 2", with a slide-out kickplate that allows you to raise the overall height from 32" up to 34" if used under more standard sized cabinets	
Built-in capable	Front-breathing design allows you to make the best use of space by installing your appliance under the counter and flush with other cabinets in 24" wide openings	
Stainless steel drawers	Drawer interiors and exteriors are fully constructed from 304 grade stainless steel for lasting durability with a finished front for an elegant look	
Professional handles	Sleek stainless steel handles add an elegant touch to any setting	
Frost-free	No-frost operation for minimum user maintenance	



ASDR2414PNR Specifications:

Overview			
Nominal Height	32.0" (81 cm)		
Height of Cabinet	32.0" (81 cm)		
Nominal Width	24.0" (61 cm)		
Width	23.38" (59 cm)		
Nominal Depth	18.0" (46 cm)		
Depth	17.88" (45 cm)		
Depth with door at 90°	29.63" (75 cm)		
Capacity	3.1 cu.ft. (88 L)		
Defrost Type	Frost-Free		
Door	Stainless Steel/Panel- Ready		
Cabinet	Black		
US Electrical Safety	ETL		
Canadian Electrical Safety	ETL-C		
Sanitation	ETL-S		
Energy Usage/Year	285.0kWh/year		
Amps	1.0		
Voltage/Frequency	115 V AC/60 Hz		
Weight	106.0 lbs. (48 kg)		
Parts & Labor Warranty	1 Year		
Compressor Warranty	5 Years		
UPC	761101088938		
Refrigerator Features			
Sabbath Mode	Yes		
Door Swing	Drawer		
Height Adjustable	Yes		
Thermostat Type	Digital		
Fan Type	Interior and Exterior		
Refrigerant Type	R600a		
Refrigerant Amount	1.38oz.		
High Side PSI	270.0		
Low Side PSI	105.0		
Level Legs Qty	4		
Interior Light	Yes		
Temperature Range	36 to 43°F		
Sound Level	33 dB		

Drawer Dimensions			
Interior Height 1	8.0" (20 cm)		
Interior Width 1	17.63" (45 cm)		
Interior Depth 1	11.25" (29 cm)		
Interior Height 2	8.0" (20 cm)		
Interior Width 2	17.63" (45 cm)		
Interior Depth 2	11.25" (29 cm)		
Dimensions			
Compressor Step Height	3.75" (10 cm)		
Compressor Step Width	17.63" (45 cm)		
Compressor Step Depth	4.75" (12 cm)		





Adj. Kickplate Extension 2" Max