accuc@ld

ARG3PV-CRT



34" x 18.5" x 19" (H x W x D)

Performance series 3 cu.ft. upright glass door controlled room temperature cabinet for pharmaceuticals and vaccines in a white finish with lock and antimicrobial silverion handle

Highlights:

Controlled room temperature cabinet to store medication, pharmaceuticals, and other sensitive materials at 72°F

Adjustable operating control range from 68 to 77°F (preset to 72°F)

Intelligent microprocessor digital temperature controller

Product Features:

| Controlled Room Temperature Cabinet | Purpose-built design to store medication, pharmaceuticals, and other sensitive materials at 72°F | |
|--|---|--|
| Purpose-built design | Designed and purpose-built to support manufacturer recommendations for storage of pharmacy, medication, and vaccines within 20° - 25°C (68° - 77°F) as defined by USP 1079> Good Storage and Distribution Practices for Drug Products | |
| +/-1.5°C Variation | The published temperature variation is derived from the maximum deviation of an NTC sensor in a 1 oz. vial located nearest the chamber geometric center during a 24 hour test period | |
| Stable operation | Designed to maintain a set temperature, even when ambient room temperature is as cold as 68°F or as high as 86°F | |
| Antimicrobial silver ion-coated handle | Powder-coated handle with naturally occurring silver ions to help reduce germ spread | |
| Adjustable temperature | Intuitive controls let you adjust the interior temperature between +68 to +77°F | |
| Temperature alarm | Visual and audible alarms alert if the interior temperature rises or falls out of set range | |
| Remote alarm contacts | Electronic controller is equipped with a volt-free contact for alarm forwarding to an external remote system (contacts located in the external rear of the unit) | |
| Automatic defrost with adjustable cycle definant APPLIANCE DIVISION, FELIX STOR 770 Garrison Avenue Bronx NY 10474 USA TEL 718 | \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\ | |

accuc@ld

ARG3PV-CRT Specifications:

| Overview | |
|-------------------------------|-----------------------------|
| Nominal Height | 34.0" (86 cm) |
| Height of Cabinet | 34.0" (86 cm) |
| Nominal Width | 19.0" (48 cm) |
| Width | 18.5" (47 cm) |
| Width with Door Open | 19.0" (48 cm) |
| Nominal Depth | 19.0" (48 cm) |
| Depth | 19.0" (48 cm) |
| Depth with Handle | 20.75" (53 cm) |
| Depth with door at 90° | 36.0" (91 cm) |
| Capacity | 3.0 cu.ft. (85 L) |
| Defrost Type | Automatic |
| Door | Glass |
| Cabinet | White |
| US Electrical Safety | ETL |
| Canadian Electrical Safety | ETL-C |
| Amps | 0.6 |
| Voltage/Frequency | 115 V AC/60 Hz |
| Weight | 87.0 lbs. (39 kg) |
| Parts & Labor Warranty | 2 Years |
| Compressor Warranty | 5 Years |
| UPC | 761101090443 |
| Refrigerator Features | |
| Door Swing | RHD |
| Reversible | Yes |
| Shelf Type | Wire |
| Shelf Qty | 4 |
| Adjustable Shelves | Yes |
| Thermostat Type | Digital |
| Fan Type | Interior |
| Refrigerant Type | R600a |
| Refrigerant Amount | 1.06oz. |
| Interior Light | Yes |
| Temperature Range | 68 to 77°F (preset to 72°F) |
| Sound Level | 37.6 dB |

| Dimensions | |
|---------------------------|----------------|
| Interior Height | 28.38" (72 cm) |
| Interior Width | 15.25" (39 cm) |
| Interior Depth | 11.75" (30 cm) |
| Compressor Step Height | 8.0" (20 cm) |
| Compressor Step Width | 15.25" (39 cm) |
| Compressor Step Depth | 3.75" (10 cm) |



