accucold

ARS8PV-CRT



Product Features:

Controlled Room Temperature Cabinet Purpose-built design to store medication, pharmaceuticals, and other sensitive materials at 72ºF Designed and purpose-built to support manufacturer recommendations for storage of Purpose-built design pharmacy, medication, and vaccines within 20° - 25°C (68° - 77°F) as defined by USP 1079> Good Storage and Distribution Practices for Drug Products The published temperature variation is derived from the maximum deviation of an NTC sensor +/-1.5°C Variation in a 1 oz. vial located nearest the chamber geometric center during a 24 hour test period Stable operation Designed to maintain a set temperature, even when ambient room temperature is as cold as 68°F or as high as 86°F Antimicrobial silver ion-coated handle Powder-coated handle with naturally occurring silver ions to help reduce the spread of germs Adjustable temperature Intuitive controls let you adjust the interior temperature between +68 to +77°F Temperature alarm Visual and audible alarms alert if the interior temperature rises or falls out of set range Remote alarm contacts Electronic controller is equipped with a volt-free contact for alarm forwarding to an external remote system (contacts located in the external rear of the unit)

Automatic defrost with adjustable cycle Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup definent APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

50" x 23.38" x 24.38" (H x W x D)

Performance series 8 cu.ft. upright controlled room temperature cabinet for pharmaceuticals and vaccines in a white finish with lock and antimicrobial silver-ion handle

Highlights:

Controlled room temperature cabinet to store medication, pharmaceuticals, and other sensitive materials at 72°F

Intelligent microprocessor digital temperature controller

Adjustable operating control range from 68 to 77°F (preset to 72°F)

accucold

ARS8PV-CRT Specifications:

| Overview | |
|-------------------------------|-----------------------------|
| Nominal Height | 50.0" (127 cm) |
| Height of Cabinet | 50.0" (127 cm) |
| Nominal Width | 24.0" (61 cm) |
| Width | 23.38" (59 cm) |
| Width with Door Open | 23.88" (61 cm) |
| Nominal Depth | 25.0" (64 cm) |
| Depth | 24.38" (62 cm) |
| Depth with Handle | 26.13" (66 cm) |
| Depth with door at 90° | 46.5" (118 cm) |
| Capacity | 8.0 cu.ft. (227 L) |
| Defrost Type | Automatic |
| Door | White |
| Cabinet | White |
| US Electrical Safety | ETL |
| Canadian Electrical Safety | ETL-C |
| Amps | 1.4 |
| Voltage/Frequency | 115 V AC/60 Hz |
| Weight | 166.0 lbs. (75 kg) |
| Parts & Labor Warranty | 2 Years |
| Compressor Warranty | 5 Years |
| UPC | 761101090566 |
| Refrigerator Features | |
| Door Swing | RHD |
| Reversible | Yes |
| Shelf Type | Wire |
| Shelf Qty | 7 |
| Adjustable Shelves | Yes |
| Thermostat Type | Digital |
| Fan Type | Interior |
| Refrigerant Type | R600a |
| Refrigerant Amount | 1.73oz. |
| Interior Light | Yes |
| Temperature Range | 68 to 77ºF (preset to 72ºF) |
| Dimensions | |
| | |

| Interior Height | 41.25" (105 cm) |
|---------------------------|-----------------|
| Interior Width | 20.0" (51 cm) |
| Interior Depth | 17.0" (43 cm) |
| Compressor Step Height | 6.5" (17 cm) |
| Compressor Step Width | 20.0" (51 cm) |
| Compressor Step Depth | 5.0" (13 cm) |
| | |





