



HC20BBADA



5.5" x 20" x 20" (H x W x D)

20 inch wide ADA compliant under cabinet convertible range hood for ducted or ductless use in black, made in North America with a remote wall switch

Highlights:

ADA compliant design allows you to control the hood from a wall light switch for easier accessibility

20 inch wide pairs well with a variety of ranges and cooktops

Made in North America in a TAA designated country

Product Features:

| | |
|-----------------------------------|--|
| 20" Wide ADA Compliant Range Hood | Convertible hood designed for ducted or ductless installation in compliant with ADA guidelines |
| ADA compliant design | Hood is wired to run off a wall switch for improved accessibility, with a remote terminal block included |
| Under cabinet range hood | Low profile design offers classic style to finish your kitchen |
| 20 inch width | Sized for use over 20 inch cooking surfaces (additional sizes available) |
| Convertible design | Can be used for ducted venting to the outside or recirculating ventilation where no external venting is possible |
| Powerful ventilation | Can operate at 270 CFM to ensure thorough ventilation of your cooking surface |
| Black finish | Matte finish in jet black suits any kitchen space |
| Easy conversion | Ships pre-set for recirculating mode but can be converted in a few simple steps |
| Versatile top or rear exhaust | Can be connected to 3 1/4" x 10" vertical or horizontal exterior venting or 7" round vertical (transition required for both) |



HC20BBADA Specifications:

| Overview | |
|----------------------------|--------------------------------------|
| Nominal Height | 6.0" (15 cm) |
| Height of Cabinet | 5.5" (14 cm) |
| Nominal Width | 20.0" (51 cm) |
| Width | 20.0" (51 cm) |
| Nominal Depth | 20.0" (51 cm) |
| Depth | 20.0" (51 cm) |
| Cabinet | Black |
| US Electrical Safety | ETL |
| Canadian Electrical Safety | ETL-C |
| Amps | 1.7 |
| Voltage/Frequency | 115 V AC/60 Hz |
| Weight | 11.0 lbs. (5 kg) |
| Parts & Labor Warranty | 1 Year |
| UPC | 761101107196 |
| Range Hood | |
| Installation | Under Cabinet |
| Venting | Convertible |
| Number of Fan Speeds | 2 |
| Maximum Air Movement | 270.0 CFM |
| Sone Rating | 6 |
| Duct Shape | 3"1/4" x 10" rectangular or 7" round |

