accucold

AFZ1PV



Product Features:

Performance Series freezer Purpose-built all-freezer for vaccine storage in medical, pharmaceutical, and life science applications Purpose-built design Designed and purpose-built for pharmacy, medication, and vaccine applications to support meeting CDC/VFC/VFA guidelines +/-1°C Variation The published temperature variation is derived from the maximum deviation of an NTC sensor in a 1 oz. vial located nearest the chamber geometric center during a 24 hour test period Adjustable temperature Intuitive controls let you adjust the interior temperature between -30°C to -10°C Temperature alarm Visual and audible alarms alert if the interior temperature rises or falls out of set range Remote alarm contacts Electronic controller is equipped with a volt-free contact for alarm forwarding to an external remote system (contacts located in the external rear of the unit) Manual defrost operation Static cooling system for an efficient and stable interior Access port Includes a pre-installed 1/2" probe hole in the right interior wall to allow easier connection to user-provided monitoring equipment Open door alarm Alarm will sound if the door is left ajar for over 4 minutes (adjustable from 1-99 minutes)

SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

22.25" x 18.5" x 23.25" (H x W x D)

Performance series Pharma-Vac 1.4 cu.ft. countertop purpose-built vaccine storage freezer

Highlights:

Intelligent microprocessor digital temperature controller

Improved temperature accuracy with a separate temperature probe for continuous product readout to simulate stored product temperature

Additional sensor reads interior air temperature for superior temperature control



accuceld

AFZ1PV Specifications:

Overview	
Nominal Height	23.0" (58 cm)
Height of Cabinet	22.25" (57 cm)
Nominal Width	19.0" (48 cm)
Width	18.5" (47 cm)
Width with Door Open	18.88" (48 cm)
Nominal Depth	24.0" (61 cm)
Depth	23.25" (59 cm)
Depth with Handle	24.75" (63 cm)
Depth with door at 90°	42.5" (108 cm)
Capacity	1.4 cu.ft. (40 L)
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Amps	1.3
Voltage/Frequency	115 V AC/60 Hz
Weight	73.0 lbs. (33 kg)
Parts & Labor Warranty	2 Years
Compressor Warranty	5 Years
UPC	761101106632
Freezer	
Door Swing	RHD
Reversible	
	Yes
Interior Height	16.5" (42 cm)
Interior Height Interior Width	
	16.5" (42 cm)
Interior Width	16.5" (42 cm) 15.25" (39 cm)
Interior Width Interior Depth	16.5" (42 cm) 15.25" (39 cm) 15.75" (40 cm)
Interior Width Interior Depth Shelf Type	16.5" (42 cm) 15.25" (39 cm) 15.75" (40 cm) Wire
Interior Width Interior Depth Shelf Type Shelf Qty	16.5" (42 cm) 15.25" (39 cm) 15.75" (40 cm) Wire 2
Interior Width Interior Depth Shelf Type Shelf Qty Adjustable Shelves	16.5" (42 cm) 15.25" (39 cm) 15.75" (40 cm) Wire 2 Yes
Interior Width Interior Depth Shelf Type Shelf Qty Adjustable Shelves Thermostat Type	16.5" (42 cm) 15.25" (39 cm) 15.75" (40 cm) Wire 2 Yes Digital
Interior Width Interior Depth Shelf Type Shelf Qty Adjustable Shelves Thermostat Type Interior Light	16.5" (42 cm) 15.25" (39 cm) 15.75" (40 cm) Wire 2 Yes Digital Yes
Interior Width Interior Depth Shelf Type Shelf Qty Adjustable Shelves Thermostat Type Interior Light Refrigerant Type	16.5" (42 cm) 15.25" (39 cm) 15.75" (40 cm) Wire 2 Yes Digital Yes R290
Interior Width Interior Depth Shelf Type Shelf Qty Adjustable Shelves Thermostat Type Interior Light Refrigerant Type Refrigerant Amount	16.5" (42 cm) 15.25" (39 cm) 15.75" (40 cm) Wire 2 Yes Digital Yes R290 0.85 oz.
Interior Width Interior Depth Shelf Type Shelf Qty Adjustable Shelves Thermostat Type Interior Light Refrigerant Type Refrigerant Amount High Side PSI	16.5" (42 cm) 15.25" (39 cm) 15.75" (40 cm) Wire 2 Yes Digital Yes R290 0.85 oz. 280.0

Compressor Step Depth	4.25" (11 cm)
Temperature Range	-30 to -10°C



