accucold

ARS2MLMC



Product Features:

MOMCUBE Breast Milk Refrigerator Countertop all-refrigerator designed for the safe and secure storage of breast milk in accordance with the CDC's guidelines Purpose-built design Designed and purpose-built for breast milk storage Adjustable temperature Intuitive controls let you adjust the interior temperature between 33 to 40°F Microprocessor control panel Digital controls with a large LED readout in Celsius or Fahrenheit for intuitive temperature management Antimicrobial silver ion-coated handle Powder-coated handle with naturally occurring silver ions to help reduce germ spread Visual and audible alarms alert if the interior temperature rises or falls out of set range Temperature alarm Remote alarm contacts Electronic controller is equipped with a volt-free contact for alarm forwarding to an external remote system (contacts located in the external rear of the unit) Automatic defrost with adjustable cycle Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup defrost Includes a pre-installed 1/2" probe hole in the right interior wall to allow easier connection to Access port user-provided monitoring equipment

SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

22.25" x 18.5" x 23.25" (H x W x D)

Purpose-built all-refrigerator for breast milk storage with 2 adjustable shelves, antimicrobial silver-ion handle, and a hospital grade cord with 'green dot' plug

Highlights:

Designed for use in NICUs, hospitals, maternity wards, lactation rooms, mothers' suites, and other facilities

Purpose-built for environments complying with Section 4207 of the Patient Protection and Affordable Care Act


Powder-coated handle with naturally occurring silver ions to help reduce germ spread

accucold

ARS2MLMC Specifications:

Overview	
Height of Cabinet	22.25" (57 cm)
Width	18.5" (47 cm)
Width with Door Open	18.88" (48 cm)
Depth	23.25" (59 cm)
Depth with Handle	24.75" (63 cm)
Depth with door at 90°	42.5" (108 cm)
Capacity	1.94 cu.ft. (55 L)
Defrost Type	Automatic
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Amps	0.6
Voltage/Frequency	115 V AC/60 Hz
Weight	80.0 lbs. (36 kg)
Parts & Labor Warranty	2 Years
Compressor Warranty	5 Years
UPC	761101106946
Refrigerator Features	
Door Swing	RHD
Reversible	Yes
Shelf Type	Wire
Shelf Qty	2
Adjustable Shelves	Yes
Thermostat Type	Digital
Fan Type	Interior
Refrigerant Type	R600a
Refrigerant Amount	0.84oz.
High Side PSI	280.0
Low Side PSI	90.0
Interior Light	Yes
Temperature Range	33 to 40°F
Dimensions	
Interior Height	16.5" (42 cm)
Interior Width	15.25" (39 cm)
Interior Depth	15.75" (40 cm)
Compressor Step Height	8.25" (21 cm)
Compressor Step Width	15.25" (39 cm)

		-"ji∾ 72" ELEC C ORD,
Compressor Step Depth	4.25" (11 cm)	
		FROM



-184

SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

