

# SBC7BRSCF2



#### 33.5" x 23.63" x 22.38" (H x W x D)

24" wide commercially approved cold brew coffee dispenser made in Europe with a twin tap kit to store and serve from two 1/6 kegs; includes adjustable legs and caster set for optional mobility

#### **Highlights:**

Made in Europe

Dual tap system lets you serve from two sixtel kegs

Designed for recessed installation or portable use with a caster set included

### **Product Features:**

24" Wide Cold Brew Coffee Dispenser	Kegerator includes all of the equipment you need to serve cold brew coffee from two sixtel kegs	
Made in Europe & the USA	Refrigeration unit is constructed in Europe and designed and modified in the USA	
Versatile use	Approved for both residential and commercial settings	
Commercially listed	ETL-S listed to ANSI-NSF Standard 7 for commercial use	
Complete dual tap coffee kit	Commercial grade tap kit includes a dual tap stainless steel draft tower, Nitrogen tank, regulator, and connections for ball lock cornelius kegs	
Dual tap system	Twin draft tower allows you to serve from two 1/6 (sixtel) sized kegs	
Slim counter height dimensions for recess or freestanding use	sed Ideal 24" footprint for an easy fit	
Height adjustable	Adjustable legs allow you to set the height anywhere between 33.5" and 34.5" to best fit under your counter	
Leg shield included	Removable cover that lets you fill the gap that can appear between the refrigerator's kickplate and floor when raising the height	
SUMMIT APPLIANCE DIVISION, FELIX STOF 770 Garrison Avenue Bronx, NY 10474 USA TEL 71		



## SBC7BRSCF2 Specifications:

Overview	
Nominal Height	34.0" (86 cm)
Height of Cabinet	33.5" (85 cm)
Nominal Width	24.0" (61 cm)
Width	23.63" (60 cm)
Nominal Depth	23.0" (58 cm)
Depth	22.38" (57 cm)
Depth with Handle	24.0" (61 cm)
Depth with door at 90°	44.25" (112 cm)
Capacity	5.3 cu.ft. (150 L)
Defrost Type	Automatic
Door	Stainless Steel
Cabinet	Black
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Energy Usage/Year	293.0kWh/year
Amps	0.8
Voltage/Frequency	115 V AC/60 Hz
Weight	100.0 lbs. (45 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101106144
Kegerator	
Door Swing	RHD
Reversible	Yes
Height Adjustable	Yes
Tap Kit	Yes
Number of Taps	2
Adjustable Shelves	Yes
Shelf Type	Glass and Scalloped
Shelf Qty	4
Thermostat Type	Dial
Interior Light	Yes
Refrigerant	R600a
Refrigerant Amount	0.64 oz.
Inter Height	27.75" (70 cm)
Interior Width	21.0" (53 cm)

Interior Depth	18.0" (46 cm)
Compressor Step Height	5.5" (14 cm)
Compressor Step Width	21.0" (53 cm)
Compressor Step Depth	6.0" (15 cm)
Level Legs Qty	4
Wheel Qty	4
Temperature Range	36 to 46°F



