

SBC7BRSIFCM2



33.5" x 23.63" x 22.38" (H x W x D)

24" wide commercially approved cold brew/nitro dispenser made in Europe with a twin tap kit to store and serve from two 1/6 kegs; includes panel-ready door, adjustable legs, and caster set for optional mobility

Highlights:

- Made in Europe
- Dual tap system lets you serve both regular cold brew and nitro coffee
- Panel-ready door lets you customize the unit to best match your style

Product Features:

24" Wide Cold Brew/Nitro Coffee Dispenser	Kegerator includes all of the equipment you need to serve cold brew and nitro coffee from two sixtel or Cornelius kegs
Made in Europe & the USA	Refrigeration unit is constructed in Europe and designed and modified in the USA
Versatile use	Approved for both residential and commercial settings
Commercially listed	ETL-S listed to ANSI-NSF Standard 7 for commercial use
Panel-ready door	Integrated stainless steel door frame allows you to mount full overlay panels over the door to create a custom look that can blend into cabinetry with no exposed frame (panel size: 23 5/16" W x 28 1/4" H and at least 3/4" thick; maximum weight: 10 lbs.)
Dispenses both flat and nitro coffee	Unique combination stout and standard tap system allows you to serve both flat iced cold brew and nitro drafts
Complete cold brew tap kit included	Commercial grade tap kit includes a dual tap stainless steel draft tower, Nitrogen tank, regulator, and connections for ball lock cornelius kegs
Dual tap system	Twin draft tower allows you to serve from two 1/6 (sixel) sized kegs

Slim counter height dimensions for recessed Ideal 24" footprint for an easy fit or freestanding use

SBC7BRSIFCM2 Specifications:

Overview	
Nominal Height	34.0" (86 cm)
Height of Cabinet	33.5" (85 cm)
Nominal Width	24.0" (61 cm)
Width	23.63" (60 cm)
Nominal Depth	23.0" (58 cm)
Depth	22.38" (57 cm)
Depth with door at 90°	44.25" (112 cm)
Capacity	5.3 cu.ft. (150 L)
Defrost Type	Automatic
Door	Integrated Frame
Cabinet	Black
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Energy Usage/Year	293.0kWh/year
Amps	0.8
Voltage/Frequency	115 V AC/60 Hz
Weight	100.0 lbs. (45 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101106212
Keerator	
Door Swing	RHD
Reversible	Factory Reversible
Height Adjustable	Yes
Tap Kit	Yes
Number of Taps	2
Adjustable Shelves	Yes
Shelf Type	Glass and Scalloped
Shelf Qty	4
Thermostat Type	Dial
Interior Light	Yes
Refrigerant	R600a
Refrigerant Amount	0.64 oz.
Inter Height	27.75" (70 cm)
Interior Width	21.0" (53 cm)
Interior Depth	18.0" (46 cm)

Compressor Step Height	5.5" (14 cm)
Compressor Step Width	21.0" (53 cm)
Compressor Step Depth	6.0" (15 cm)
Level Legs Qty	4
Wheel Qty	4
Temperature Range	36 to 46°F

