

## SBC7BRSIFCF2LHD



33.5" x 23.63" x 22.38" (H x W x D)

24" wide commercially approved cold brew dispenser made in Europe with a twin tap kit to store and serve from two 1/6 kegs; includes panel-ready door, adjustable legs, and caster set for optional mobility

## **Highlights:**

Made in Europe

Dual tap system lets you serve cold brew coffee from two separate kegs

Panel-ready door lets you customize the unit to best match your style

## **Product Features:**

24" Wide Cold Brew Coffee Dispenser	Kegerator includes all of the equipment you need to serve coffee from two sixtel kegs	
Made in Europe & the USA	Refrigeration unit is constructed in Europe and designed and modified in the USA	
Versatile use	Approved for both residential and commercial settings	
Commercially listed	ETL-S listed to ANSI-NSF Standard 7 for commercial use	
Panel-ready door	Integrated stainless steel door frame allows you to mount full overlay panels over the door to create a custom look that can blend into cabinetry with no exposed frame (panel size: 23 5/16" W x 28 1/4" H and at least 3/4" thick; maximum weight: 10 lbs.)	
Complete cold brew tap kit included	Commercial grade tap kit includes a dual tap stainless steel draft tower, Nitrogen tank, regulator, and connections for ball lock cornelius kegs	
Dual tap system	Twin draft tower allows you to serve from two 1/6 (sixtel) sized kegs	
Slim counter height dimensions for recessed or freestanding use	d Ideal 24" footprint for an easy fit	
Height adjustable	Adjustable legs allow you to set the height anywhere between 33.5" and 34.5" to best fit under your counter	







## SBC7BRSIFCF2LHD Specifications:

Overview			
Nominal Height	34.0" (86 cm)		
Height of Cabinet	33.5" (85 cm)		
Nominal Width	24.0" (61 cm)		
Width	23.63" (60 cm)		
Nominal Depth	23.0" (58 cm)		
Depth	22.38" (57 cm)		
Depth with door at 90°	44.25" (112 cm)		
Capacity	5.3 cu.ft. (150 L)		
Defrost Type	Automatic		
Door	Integrated Frame		
Cabinet	Black		
US Electrical Safety	ETL		
Canadian Electrical Safety	ETL-C		
Sanitation	ETL-S		
Energy Usage/Year	293.0kWh/year		
Amps	0.8		
Voltage/Frequency	115 V AC/60 Hz		
Weight	100.0 lbs. (45 kg)		
Parts & Labor Warranty	1 Year		
Compressor Warranty	5 Years		
UPC	761101106298		
Kegerator			
Door Swing	LHD		
Reversible	No		
Height Adjustable	Yes		
Tap Kit	Yes		
Number of Taps	2		
Adjustable Shelves	Yes		
Shelf Type	Glass and Scalloped		
Shelf Qty	4		
Thermostat Type	Dial		
Interior Light	Yes		
Refrigerant	R600a		
Refrigerant Amount	0.64 oz.		
Inter Height	27.75" (70 cm)		
Interior Width	21.0" (53 cm)		
Interior Depth	18.0" (46 cm)		

Compressor Step Height	5.5" (14 cm)
Compressor Step Width	21.0" (53 cm)
Compressor Step Depth	6.0" (15 cm)
Level Legs Qty	4
Wheel Qty	4
Temperature Range	36 to 46°F





