

ACR21W



23.13" x 18.88" x 21.38" (H x W x D)

Compact healthcare all-refrigerator with self-closing glass door, front lock, digital controls, and external temperature readout

Highlights:

Designed and constructed for reliable cold storage in healthcare facilities

External temperature readout of the current and high/low temperatures

User-friendly front control panel keeps the thermostat and alarm in reach without having to open the door

Product Features:

Switched from Celsius to Fahrenheit at the touch of a button High/low temperature alarm Audible alarm sounds if the interior temperature rises or falls out of set range Thermometer probe is encased in a glass bead-filled bottle and stored in a fixed box center shelf. This is the ideal way to produce temperature readings closest to stored as recommended by the CDC, VFC and VFA's guidelines	QTemp Medical Refrigerator	All-refrigerator designed to operate between 2 and 8°C for a variety of storage application in medical offices and other healthcare facilities	
External temperature readout Includes continuous display of the current interior and high/low temperature, and can switched from Celsius to Fahrenheit at the touch of a button High/low temperature alarm Audible alarm sounds if the interior temperature rises or falls out of set range Thermometer probe is encased in a glass bead-filled bottle and stored in a fixed box center shelf. This is the ideal way to produce temperature readings closest to stored as recommended by the CDC, VFC and VFA's guidelines Access port 3/8" probe hole with cover is pre-installed in unit's side to allow easy installation of us provided monitoring equipment	emperature Range: 2º to 8ºC	Preset to 5°C as recommended for many storage applications	
Switched from Celsius to Fahrenheit at the touch of a button High/low temperature alarm Audible alarm sounds if the interior temperature rises or falls out of set range Thermometer probe is encased in a glass bead-filled bottle and stored in a fixed box center shelf. This is the ideal way to produce temperature readings closest to stored as recommended by the CDC, VFC and VFA's guidelines Access port 3/8" probe hole with cover is pre-installed in unit's side to allow easy installation of us provided monitoring equipment	ompact size	Full 1.94 cu.ft. capacity inside conveniently slim footprint	
Buffered temperature probe Thermometer probe is encased in a glass bead-filled bottle and stored in a fixed box center shelf. This is the ideal way to produce temperature readings closest to stored as recommended by the CDC, VFC and VFA's guidelines Access port 3/8" probe hole with cover is pre-installed in unit's side to allow easy installation of us provided monitoring equipment	cternal temperature readout	Includes continuous display of the current interior and high/low temperature, and can be switched from Celsius to Fahrenheit at the touch of a button	
center shelf. This is the ideal way to produce temperature readings closest to stored as recommended by the CDC, VFC and VFA's guidelines Access port 3/8" probe hole with cover is pre-installed in unit's side to allow easy installation of us provided monitoring equipment	gh/low temperature alarm	Audible alarm sounds if the interior temperature rises or falls out of set range	
provided monitoring equipment	uffered temperature probe	Thermometer probe is encased in a glass bead-filled bottle and stored in a fixed box on the center shelf. This is the ideal way to produce temperature readings closest to stored content as recommended by the CDC, VFC and VFA's guidelines	
Factory installed lock Keyed lock for a secure interior (2 keys included)	ccess port	3/8" probe hole with cover is pre-installed in unit's side to allow easy installation of user- provided monitoring equipment	
	actory installed lock	Keyed lock for a secure interior (2 keys included)	
Automatic defrost Reduced user maintenance with automatic defrost	utomatic defrost	Reduced user maintenance with automatic defrost	



ACR21W Specifications:

Overview	
Nominal Height	24.0" (61 cm)
Height of Cabinet	23.13" (59 cm)
Nominal Width	19.0" (48 cm)
Width	18.88" (48 cm)
Width with Door Open	19.38" (49 cm)
Nominal Depth	22.0" (56 cm)
Depth	21.38" (54 cm)
Depth with door at 90°	38.75" (98 cm)
Capacity	1.94 cu.ft. (55 L)
Defrost Type	Automatic
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Amps	0.9
Voltage/Frequency	115 V AC/60 Hz
Weight	48.5 lbs. (22 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101082929
Refrigerator Features	
Door Swing	RHD
Reversible	Factory Reversible
Shelf Type	Wire
Shelf Qty	1
Thermostat Type	Digital
Fan Type	Interior
Refrigerant Type	R600a
Refrigerant Amount	0.85oz.
High Side PSI	1.45
Low Side PSI	0.85
Level Legs Qty	2
Interior Light	Yes
Temperature Range	2º to 8ºC
Sound Level	36.3 dB
Dimensions	
Interior Height	16.25" (41 cm)

Interior Width	15.5" (39 cm)
Interior Depth	14.5" (37 cm)
Compressor Step Height	6.5" (17 cm)
Compressor Step Width	15.5" (39 cm)
Compressor Step Depth	5.5" (14 cm)





