

ACR161WNSF456LHD



22.88" x 18.75" x 18.38" (H x W x D)

Compact healthcare all-refrigerator certified to NSF/ANSI 456 with self-closing solid door, front lock, digital controls, and NIST-calibrated temperature readout

Highlights:

Certified to NSF/ANSI 456 Vaccine Storage Standard

Specially designed to meet current CDC/VFC/VFA vaccine refrigeration guidelines for convenient storage in pharmacies, medical offices, and other healthcare facilities

Designed and constructed for reliable cold storage in healthcare facilities

Product Features:

| | |
|--|---|
| EQTemp Medical Refrigerator | Refrigerator All-refrigerator designed to operate between 2 and 8°C for a variety of storage application in medical offices and other healthcare facilities |
| Certified to NSF/ANSI 456 Vaccine Storage Standard | Tested to comply with the latest standards |
| Certificate of calibration included | The temperature monitoring device (TMD) is calibrated to NIST standards in our ISO/IEC 17025:2017 certified calibration laboratory and ships with a 2-year certificate of calibration for your records |
| Temperature Range: 2° to 8°C | Preset to 5°C as recommended for many storage applications |
| Compact size | Full 1.58 cu.ft. capacity inside conveniently slim footprint |
| External temperature readout | Includes continuous display of the current interior and high/low temperature, and can be switched from Celsius to Fahrenheit at the touch of a button |
| High/low temperature alarm | Audible alarm sounds if the interior temperature rises or falls out of set range |
| Buffered temperature probe | Thermometer probe is encased in a glass bead-filled bottle and stored in a fixed box on the center shelf. This is the ideal way to produce temperature readings closest to stored contents, as recommended by the CDC, VFC and VFA's guidelines |

ACR161WNSF456LHD Specifications:

| Overview | |
|----------------------------|--------------------|
| Nominal Height | 23.0" (58 cm) |
| Height of Cabinet | 22.88" (58 cm) |
| Nominal Width | 19.0" (48 cm) |
| Width | 18.75" (48 cm) |
| Width with Door Open | 19.25" (49 cm) |
| Nominal Depth | 19.0" (48 cm) |
| Depth | 18.38" (47 cm) |
| Depth with door at 90° | 35.63" (91 cm) |
| Capacity | 1.58 cu.ft. (45 L) |
| Defrost Type | Automatic |
| Door | White |
| Cabinet | White |
| US Electrical Safety | ETL |
| Canadian Electrical Safety | ETL-C |
| Sanitation | ETL-S to NSF 456 |
| Amps | 0.6 |
| Voltage/Frequency | 115 V AC/60 Hz |
| Weight | 38.0 lbs. (17 kg) |
| Parts & Labor Warranty | 1 Year |
| Compressor Warranty | 5 Years |
| UPC | 761101107660 |
| Refrigerator Features | |
| Door Swing | LHD |
| Reversible | Factory Reversible |
| Shelf Type | Wire |
| Shelf Qty | 1 |
| Thermostat Type | Digital |
| Fan Type | Interior |
| Refrigerant Type | R600a |
| Refrigerant Amount | 0.85oz. |
| High Side PSI | 1.45 |
| Low Side PSI | 0.85 |
| Level Legs Qty | 2 |
| Interior Light | Yes |
| Temperature Range | 2° to 8°C |
| Sound Level | 36.8 dB |
| Dimensions | |

| | |
|------------------------|----------------|
| Interior Height | 16.63" (42 cm) |
| Interior Width | 15.63" (40 cm) |
| Interior Depth | 12.13" (31 cm) |
| Compressor Step Height | 7.75" (20 cm) |
| Compressor Step Width | 15.63" (40 cm) |
| Compressor Step Depth | 5.25" (13 cm) |

