### SUMMIT

# SEH1524SSADA



#### 37.25" x 23.56" x 19.69" (H x W x D)

24" wide ADA-compliant European-style convertible wallmounted range hood in stainless steel with remote wall switch

#### **Highlights:**

ADA-compliant design allows you to control the hood from a wall light switch for easier accessibility

24" wide range hood ideal for apartments and other smaller kitchen spaces

Versatile design for ducted or recirculating operation with a set of carbon filters included

#### **Product Features:**

24" wide wall-mounted range hood	European style range hood designed to bring effective ventilation over 24" wide cooking surfaces
ADA-compliant design	Control panel comes on a remote terminal block to be installed according to ADA compliant guidelines for improved accessibility (some assembly required)
Convertible design with no additional purchase necessary	Can be used for ducted venting to the outside or recirculating ventilation where no external venting is possible
Charcoal filter set included	Two round carbon filters attach to the blower to absorb grease and odors when using the hood in recirculating mode
Powerful ventilation	400 CFM blower to effectively remove smoke and cooking odors from your kitchen
Cord included	Pre-installed power cord with 3-prong plug for 115V outlets
LED lighting (bulbs included)	Includes two pre-installed LED bulbs to illuminate your cooking surface
Adjustable height	Includes a telescoping chimney extender that allows you to adjust the overall height between 25 1/2" to 37 1/4"
Stainless steel finish	Durable construction in an attractive style with a horizontal grain

SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

info@summitappliance.com

 $\checkmark$ 



## SUMMIT

### SEH1524SSADA Specifications:

Nominal Height 38.0" (97 cm)   Height of Cabinet 37.25" (95 cm)   Nominal Width 24.0" (61 cm)   Width 23.56" (60 cm)   Nominal Depth 20.0" (51 cm)   Depth 19.69" (50 cm)   Door Stainless Steel   US Electrical Safety ETL   Amps 2.6   Voltage/Frequency 115 V AC/60 Hz   Weight 39.0 lbs. (18 kg)   Parts & Labor Warranty 1 Year   UPC 761101107257   Range Hood Venting   Controls Slide   Light Yes   Number of Lights 2   Light Type LED   Number of Fan Speeds 3   Maximum Air Movement 400.0 CFM   Minimum Height 25.5" (65 cm)   Maximum Height 37.25" (95 cm)	Overview	
Nominal Width 24.0" (61 cm)   Width 23.56" (60 cm)   Nominal Depth 20.0" (51 cm)   Depth 19.69" (50 cm)   Door Stainless Steel   US Electrical Safety ETL   Amps 2.6   Voltage/Frequency 115 V AC/60 Hz   Weight 39.0 lbs. (18 kg)   Parts & Labor Warranty 1 Year   UPC 761101107257   Range Hood Venting   Controls Slide   Light Yes   Number of Lights 2   Light Type LED   Number of Fan Speeds 3   Maximum Air Movement 400.0 CFM   Minimum Height 37.25" (95 cm)	Nominal Height	38.0" (97 cm)
Width23.56" (60 cm)Nominal Depth20.0" (51 cm)Depth19.69" (50 cm)DoorStainless SteelUS Electrical SafetyETLAmps2.6Voltage/Frequency115 V AC/60 HzWeight39.0 lbs. (18 kg)Parts & Labor Warranty1 YearUPC761101107257Range HoodUlageInstallationWall-MountedVentingConvertibleControlsSlideLightYesNumber of Lights2Light TypeLEDNumber of Fan Speeds3Maximum Air Movement400.0 CFMMinimum Height37.25" (95 cm)	Height of Cabinet	37.25" (95 cm)
Nominal Depth20.0" (51 cm)Depth19.69" (50 cm)DoorStainless SteelUS Electrical SafetyETLAmps2.6Voltage/Frequency115 V AC/60 HzWeight39.0 lbs. (18 kg)Parts & Labor Warranty1 YearUPC761101107257Range HoodUInstallationWall-MountedVentingConvertibleControlsSlideLightYesNumber of Lights2Light TypeLEDNumber of Fan Speeds3Maximum Air Movement400.0 CFMMinimum Height37.25" (95 cm)	Nominal Width	24.0" (61 cm)
Depth19.69" (50 cm)DoorStainless SteelUS Electrical SafetyETLAmps2.6Voltage/Frequency115 V AC/60 HzWeight39.0 lbs. (18 kg)Parts & Labor Warranty1 YearUPC761101107257Range HoodInstallationWall-MountedVentingConvertibleControlsSlideLightYesNumber of Lights2Light TypeLEDNumber of Fan Speeds3Maximum Air Movement400.0 CFMMinimum Height37.25" (95 cm)	Width	23.56" (60 cm)
DoorStainless SteelUS Electrical SafetyETLAmps2.6Voltage/Frequency115 V AC/60 HzWeight39.0 lbs. (18 kg)Parts & Labor Warranty1 YearUPC761101107257Range HoodInstallationWall-MountedVentingConvertibleControlsSlideLightYesNumber of Lights2Light TypeLEDNumber of Fan Speeds3Maximum Air Movement400.0 CFMMinimum Height37.25" (95 cm)	Nominal Depth	20.0" (51 cm)
US Electrical SafetyETLAmps2.6Voltage/Frequency115 V AC/60 HzWeight39.0 lbs. (18 kg)Parts & Labor Warranty1 YearUPC761101107257Range HoodInstallationWall-MountedVentingConvertibleControlsSlideLightYesNumber of Lights2Light TypeLEDNumber of Fan Speeds3Maximum Air Movement400.0 CFMMinimum Height37.25" (95 cm)	Depth	19.69" (50 cm)
Amps2.6Voltage/Frequency115 V AC/60 HzWeight39.0 lbs. (18 kg)Parts & Labor Warranty1 YearUPC761101107257Range HoodVall-MountedInstallationWall-MountedVentingConvertibleControlsSlideLightYesNumber of Lights2Light TypeLEDNumber of Fan Speeds3Maximum Air Movement400.0 CFMMinimum Height37.25" (95 cm)	Door	Stainless Steel
Voltage/Frequency115 V AC/60 HzWeight39.0 lbs. (18 kg)Parts & Labor Warranty1 YearUPC761101107257Range HoodInstallationWall-MountedVentingConvertibleControlsSlideLightYesNumber of Lights2Light TypeLEDNumber of Fan Speeds3Maximum Air Movement400.0 CFMMinimum Height37.25" (95 cm)	US Electrical Safety	ETL
Weight39.0 lbs. (18 kg)Parts & Labor Warranty1 YearUPC761101107257Range HoodVall-MountedInstallationWall-MountedVentingConvertibleControlsSlideLightYesNumber of Lights2Light TypeLEDNumber of Fan Speeds3Maximum Air Movement400.0 CFMMinimum Height37.25" (95 cm)	Amps	2.6
Parts & Labor Warranty1 YearUPC761101107257Range HoodVall-MountedInstallationWall-MountedVentingConvertibleControlsSlideLightYesNumber of Lights2Light TypeLEDNumber of Fan Speeds3Maximum Air Movement400.0 CFMMinimum Height25.5" (65 cm)Maximum Height37.25" (95 cm)	Voltage/Frequency	115 V AC/60 Hz
UPC761101107257Range HoodVall-MountedInstallationWall-MountedVentingConvertibleControlsSlideLightYesNumber of Lights2Light TypeLEDNumber of Fan Speeds3Maximum Air Movement400.0 CFMMinimum Height25.5" (65 cm)Maximum Height37.25" (95 cm)	Weight	39.0 lbs. (18 kg)
Range HoodInstallationWall-MountedVentingConvertibleControlsSlideLightYesNumber of Lights2Light TypeLEDNumber of Fan Speeds3Maximum Air Movement400.0 CFMMinimum Height25.5" (65 cm)Maximum Height37.25" (95 cm)	Parts & Labor Warranty	1 Year
InstallationWall-MountedVentingConvertibleControlsSlideLightYesNumber of Lights2Light TypeLEDNumber of Fan Speeds3Maximum Air Movement400.0 CFMMinimum Height25.5" (65 cm)Maximum Height37.25" (95 cm)	UPC	761101107257
VentingConvertibleControlsSlideLightYesNumber of Lights2Light TypeLEDNumber of Fan Speeds3Maximum Air Movement400.0 CFMMinimum Height25.5" (65 cm)Maximum Height37.25" (95 cm)		
ControlsSlideLightYesNumber of Lights2Light TypeLEDNumber of Fan Speeds3Maximum Air Movement400.0 CFMMinimum Height25.5" (65 cm)Maximum Height37.25" (95 cm)	Range Hood	
LightYesNumber of Lights2Light TypeLEDNumber of Fan Speeds3Maximum Air Movement400.0 CFMMinimum Height25.5" (65 cm)Maximum Height37.25" (95 cm)		Wall-Mounted
Number of Lights2Light TypeLEDNumber of Fan Speeds3Maximum Air Movement400.0 CFMMinimum Height25.5" (65 cm)Maximum Height37.25" (95 cm)	Installation	
Light TypeLEDNumber of Fan Speeds3Maximum Air Movement400.0 CFMMinimum Height25.5" (65 cm)Maximum Height37.25" (95 cm)	Installation Venting	Convertible
Number of Fan Speeds3Maximum Air Movement400.0 CFMMinimum Height25.5" (65 cm)Maximum Height37.25" (95 cm)	Installation Venting Controls	Convertible
Maximum Air Movement400.0 CFMMinimum Height25.5" (65 cm)Maximum Height37.25" (95 cm)	Installation Venting Controls Light	Convertible Slide Yes
Minimum Height 25.5" (65 cm)   Maximum Height 37.25" (95 cm)	Installation Venting Controls Light Number of Lights	Convertible Slide Yes 2
Maximum Height 37.25" (95 cm)	Installation Venting Controls Light Number of Lights Light Type	Convertible Slide Yes 2 LED
	Installation Venting Controls Light Number of Lights Light Type Number of Fan Speeds	Convertible Slide Yes 2 LED 3
Duct Shape 6" Round	Installation Venting Controls Light Number of Lights Light Type Number of Fan Speeds Maximum Air Movement	Convertible Slide Yes 2 LED 3 400.0 CFM
	Installation Venting Controls Light Number of Lights Light Type Number of Fan Speeds Maximum Air Movement Minimum Height	Convertible   Slide   Yes   2   LED   3   400.0 CFM   25.5" (65 cm)



