## accuc@ld

# PTHC65GUCLHD



34.25" x 23.5" x 23.5" (H x W x D)

Undercounter single chamber passive heating blanket warmer with glass door, stainless steel interior and exterior, digital thermostat, and lock

#### **Highlights:**

Designed and assembled in the USA

No internal fans or moving parts ensure silent, safe, and efficient operation

Stainless steel interior for durable use and easy cleaning

#### **Product Features:**

| Undercounter Warming Cabinet    | 24" wide blanket warmer designed and constructed in the USA  |  |
|---------------------------------|--|--|
| 90 to 140°F temperature range   | Designed and set to keep blankets warm in hospitals, medical and physical therapy offices, spas, and other facilities                  |  |
| Passive heating                 | Fixed heaters located at the bottom of the cabinet with no fans or moving parts to minimize lint buildup for safer, more efficient use |  |
| Built-In capable                | Front-breathing design lets you make the best use of space by installing your appliance under the counter                              |  |
| Full capacity                   | 4.57 cu.ft. interior in a slim-fitting 24" footprint   |  |
| Digital thermostat              | Electronic controls are conveniently located externally for easy temperature adjustment  |  |
| Electronic readout              | Large LED temperature display ensures your staff can easily monitor the interior temperature   |  |
| Silent operation                | No moving parts to ensure a quiet performance  |  |
| Double pane tempered glass door | Heat-safe glass door offers a full view of stored contents, with a stainless steel door trim to highlight the interior                 |  |





### accuc@ld

### PTHC65GUCLHD Specifications:

| Overview                      |                     |  |
|-------------------------------|---------------------|--|
| Nominal Height                | 35.0" (89 cm)       |  |
| Height of Cabinet             | 34.25" (87 cm)      |  |
| Nominal Width                 | 24.0" (61 cm)       |  |
| Width                         | 23.5" (60 cm)       |  |
| Nominal Depth                 | 24.0" (61 cm)       |  |
| Depth                         | 23.5" (60 cm)       |  |
| Depth with Handle             | 25.38" (64 cm)      |  |
| Depth with door at 90°        | 45.75" (116 cm)     |  |
| Capacity                      | 4.57 cu.ft. (129 L) |  |
| Door                          | Glass               |  |
| Cabinet                       | Stainless Steel     |  |
| US Electrical Safety          | ETL                 |  |
| Canadian Electrical<br>Safety | ETL-C               |  |
| Amps                          | 5.5                 |  |
| Voltage/Frequency             | 115 V AC/60 Hz      |  |
| Weight                        | 90.0 lbs. (41 kg)   |  |
| Parts & Labor Warranty        | 1 Year              |  |
| UPC                           | 761101108063        |  |
| Warming Cabinet               |                     |  |
| Door Swing                    | LHD                 |  |
| Reversible                    | Factory Reversible  |  |
| Adjustable Shelves            | Yes                 |  |
| Shelf Type                    | Chrome              |  |
| Shelf Qty                     | 3                   |  |
| Thermostat Type               | Digital             |  |
| Interior Height               | 26.0" (66 cm)       |  |
| Interior Width                | 19.38" (49 cm)      |  |
| Interior Depth                | 17.38" (44 cm)      |  |
| Level Legs                    | 4                   |  |
| Dolly                         | Optional            |  |
| Temperature Range             | 90 to 140°F         |  |
|                               |                     |  |

