accuc@ld

URM19WLHD



72" x 30.5" x 27.63" (H x W x D)

Upright manual defrost refrigerator with lock and external alarm/thermometer for general purpose storage applications

Highlights:

General purpose refrigerator designed for the storage of samples, enzymes, reagents, and other laboratory and clinical materials that require a more stable interior than traditional automatic defrost

Factory-installed lock provides security you can count on

Static cooling system with manual defrost to ensure a more stable interior

Product Features:

Upright All-Refrigerator	Large capacity refrigerator with front-opening design and manual defrost operation	
Large capacity	More than 18 cu.ft. of interior space	
Manual defrost	Static cooling system with no fans or warming cycles	
Dial thermostat	Intuitive and reliable mechanical thermostat located inside the unit to prevent unnecessary adjustments	
High/low temperature alarm	Audible alarm sounds if the interior temperature rises or falls out of set range	
External temperature readout	Includes continuous display of the current interior and high/low temperature, and can be switched from Celsius to Fahrenheit at the touch of a button	
Buffered temperature probe	Thermometer probe is encased in a glass bead-filled bottle and stored in a fixed box on the center shelf. This is the ideal way to produce temperature readings closest to stored contents	
Access port	3/8" probe hole with cover is pre-installed in unit's side to allow easy installation of user-provided monitoring equipment	
Cantilevered shelving	Tight pilaster spacing throughout the interior allows you to adjust the shelf positions to meet your exact storage needs	





accuc@ld

URM19WLHD Specifications:

Overview			
Height of Cabinet	72.0" (183 cm)		
Width	30.5" (77 cm)		
Depth	27.63" (70 cm)		
Depth with Handle	30.25" (77 cm)		
Depth with door at 90°	55.38" (141 cm)		
Capacity	18.3 cu.ft. (518 L)		
Defrost Type	Manual		
Door	White		
Cabinet	White		
US Electrical Safety	ETL		
Canadian Electrical Safety	ETL-C		
Sanitation	ETL-S		
Amps	2.7		
Voltage/Frequency	115 V AC/60 Hz		
Weight	215.0 lbs. (98 kg)		
Shipping Weight	248.0 lbs. (112 kg)		
Parts & Labor Warranty	1 Year		
Compressor Warranty	5 Years		
UPC	761101144979		
Refrigerator Features			
Door Swing	LHD		
Reversible	Footomy Dovoroible		
	Factory Reversible		
Shelf Type	Wire		
Shelf Type Shelf Qty			
	Wire		
Shelf Qty	Wire 4		
Shelf Qty Full Door Shelf Qty	Wire 4 4		
Shelf Qty Full Door Shelf Qty Thermostat Type	Wire 4 4 Dial		
Shelf Qty Full Door Shelf Qty Thermostat Type Fan Type	Wire 4 4 Dial Interior		
Shelf Qty Full Door Shelf Qty Thermostat Type Fan Type Refrigerant Type	Wire 4 4 Dial Interior R290a		
Shelf Qty Full Door Shelf Qty Thermostat Type Fan Type Refrigerant Type Refrigerant Amount	Wire 4 4 Dial Interior R290a 3.88oz.		
Shelf Qty Full Door Shelf Qty Thermostat Type Fan Type Refrigerant Type Refrigerant Amount High Side PSI	Wire 4 Dial Interior R290a 3.88oz. 280.0		
Shelf Qty Full Door Shelf Qty Thermostat Type Fan Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI	Wire 4 4 Dial Interior R290a 3.88oz. 280.0 145.0		
Shelf Qty Full Door Shelf Qty Thermostat Type Fan Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI Interior Light	Wire 4 4 Dial Interior R290a 3.88oz. 280.0 145.0		
Shelf Qty Full Door Shelf Qty Thermostat Type Fan Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI Interior Light Dimensions	Wire 4 Dial Interior R290a 3.88oz. 280.0 145.0 Yes		
Shelf Qty Full Door Shelf Qty Thermostat Type Fan Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI Interior Light Dimensions Interior Height	Wire 4 Dial Interior R290a 3.88oz. 280.0 145.0 Yes		
Shelf Qty Full Door Shelf Qty Thermostat Type Fan Type Refrigerant Type Refrigerant Amount High Side PSI Low Side PSI Interior Light Dimensions Interior Height Interior Width	Wire 4 4 Dial Interior R290a 3.88oz. 280.0 145.0 Yes 64.0" (163 cm) 25.25" (64 cm)		

Compressor Step Width	25.25" (64 cm)
Compressor Step Depth	7.25" (18 cm)



