## accuceld

# **DL11BWIFIKIT**



#### 3.5" x 7.25" x 3.25" (H x W x D)

NIST calibrated wifi/Bluetooth enabled single channel digital data logger with LCD display of the current and high/low temperature and audible/visual temperature alarm

#### **Highlights:**

WiFi enabled for cloud-based recording

NIST calibrated with a certification of calibration included

Helps to meet CDC, VFC and VFA guidelines for monitoring vaccine storage temperature

#### **Product Features:**

WiFi/Bluetooth Enabled Single Channel Data Real-time monitoring with a fully enabled system to alert via the cloud Logger

-90°C to +40°C Operating Range	Wide range to accommodate a variety of storage applications	
Supports CDC guidelines recommending a "digital data logger"	Calibrated design and temperature display helps facilities meet CDC, VFC and VFA guidelines for monitoring vaccine storage	
Large storage capacity	Stores up to 16,000 readings ot 32,000 with the optional second channel	
Secure data collection	Meets FDA21 CFR Part 11	
User-friendly design	Free intuitive software for convenient logging	
Premium software tier	Optional 2-year program includes email, text, and call options	
Real-time data	Temperature readings are updated to the cloud in real time	
Temperature alarm	Audible and visual alarm will sound and indicator light will flash if temperature rises or falls below the specified approved range	

 $\checkmark$ 



## accuceld

### **DL11BWIFIKIT Specifications:**

Overview	
Nominal Height	3.5" (9 cm)
Height of Cabinet	3.5" (9 cm)
Nominal Width	8.0" (20 cm)
Width	7.25" (18 cm)
Nominal Depth	4.0" (10 cm)
Depth	3.25" (8 cm)
Voltage/Frequency	115 V AC/60 Hz
Weight	3.0 lbs. (1 kg)
Parts & Labor Warranty	1 Year
UPC	761101146737



