



# SBC58BLBIADAIFTWINCFB



32.25" x 23.63" x 22.75" (H x W x D)

Built-in undercounter ADA height commercially listed dual tap combination beer and cold brew coffee dispenser with panel-ready door and black cabinet

**Highlights:**

Uniquely versatile design lets you dispense both beer and coffee

32 inch height fits under lower ADA compliant counters

Commercially listed to NSF-7 standards

**Product Features:**

|   |   |
|---|---|
| Combination Beer + Cold Brew Coffee Kegerator | Dual tap kegerator dispenses both beer and coffee   |
| ADA compliant height                          | Sized at 32 inches high (32.25 to hinge cap) for installation under lower ADA compliant counters  |
| Commercially approved                         | ETL-S listed to NSF-7 commercial standards and meets UL-471 for use in foodservice settings   |
| Built-in capable                              | Front-breathing design lets you make the best use of space by installing your appliance under the counter   |
| Complete dual tap kit                         | Ships with a complete twin tap kit that includes a dual dispenser tower, regulators, and all the connection equipment you need to serve from a 1/6 beer or coffee keg   |
| Panel-ready door                              | Customize the front by mounting an overlay panel over the door; seamless look can blend into other cabinetry with no exposed frame. Handle not included (panel size: 23 5/16" W x 28 1/4" H and at least 3/4" thick; maximum weight: 10 lbs.) |
| Adjustable thermostat                         | Interior dial thermostat ensures easy temperature management  |
| Automatic defrost                             | No-frost operation for minimum user maintenance   |



SBC58BLBIADAIFTWINCFB Specifications:

| Overview                   |                    |
|----------------------------|--------------------|
| Nominal Height             | 32.0" (81 cm)      |
| Height of Cabinet          | 32.0" (81 cm)      |
| Height to Hinge Cap        | 32.25" (82 cm)     |
| Nominal Width              | 24.0" (61 cm)      |
| Width                      | 23.63" (60 cm)     |
| Nominal Depth              | 23.0" (58 cm)      |
| Depth                      | 22.75" (58 cm)     |
| Depth with door at 90°     | 45.0" (114 cm)     |
| Capacity                   | 5.5 cu.ft. (156 L) |
| Defrost Type               | Automatic          |
| Door                       | Panel-Ready        |
| Cabinet                    | Black              |
| US Electrical Safety       | ETL                |
| Canadian Electrical Safety | ETL-C              |
| Sanitation                 | ETL-S              |
| Amps                       | 1.2                |
| Voltage/Frequency          | 115 V AC/60 Hz     |
| Weight                     | 110.0 lbs. (50 kg) |
| Parts & Labor Warranty     | 1 Year             |
| Compressor Warranty        | 5 Years            |
| UPC                        | 761101156651       |
| Kegerator                  |                    |
| Door Swing                 | RHD                |
| Reversible                 | Factory Reversible |
| Tap Kit                    | Yes                |
| Height with Tap            | 47.5" (121 cm)     |
| Number of Taps             | 2                  |
| Thermostat Type            | Dial               |
| Interior Light             | Yes                |
| Fan Type                   | Exterior           |
| Refrigerant                | R600a              |
| Refrigerant Amount         | 0.64 oz.           |
| High Side PSI              | 180.0              |
| Low Side PSI               | 80.0               |
| Inter Height               | 25.75" (65 cm)     |
| Interior Width             | 21.0" (53 cm)      |
| Interior Depth             | 17.75" (45 cm)     |

|                        |               |
|------------------------|---------------|
| Compressor Step Height | 6.5" (17 cm)  |
| Compressor Step Width  | 21.0" (53 cm) |
| Compressor Step Depth  | 5.5" (14 cm)  |
| Temperature Range      | 34° to 43°F   |

